

IP-Ai

HAND WRAPPING SYSTEM



RICE LAKE
RETAIL SOLUTIONS

800-472-6703
www.ricelake.com/retail

IP-Ai

HAND WRAPPING SYSTEM

Premier Performance

Ishida's IP-Ai PC-based hand-wrapping system is the ideal complement to high-volume automatic wrappers. The IP-Ai is capable of fast weighing and print speeds up to 5.9 inches per second. Its front-loading large, nine-inch label roll capacity keeps businesses up and running longer. Create eye-catching labels with the ability to store and print custom graphics.

Designed to enhance visibility and productivity, the large color touch screen provides easy access to PLUs via category keys. Networking capability with Ishida's ScaleLink Pro 5 and other third-party scale management software helps maintain consistent and accurate pricing.

From ergonomic design to high-speed performance, the IP-Ai offers the latest technology to streamline prepackaging operations.

Standard Features

- Large 12.1-in color touch screen with printer and scale base
- Front-loading, 9-in (230-mm) label roll capacity
- 3-in thermal head
- Prints all legally required safe-handling, COOL and nutritional information
- Stores and prints graphics for custom labeling
- Ethernet communications
- Adjustable touch screen viewing angle
- 19 tactile keys
- 2 GB of memory
- Over 30 selectable fixed bar code formats
- Flexible setup for ergonomic operation
- Compatible with third-party communication software, including Invatron's PLUM™ and ADC's InterScale™

Options and Accessories

- ScaleLink Pro 5 scale management software
- Wrap station configurations and all-purpose shelf for Scalemate, (W x D) 14 in x 34 in
- Internal RF communication



Shown with optional equipment

Your Rice Lake Weighing Systems distributor is:

IP-Ai label drawer



Specifications

Weighing Capacity (Dual Range):	0-15 x 0.005 lb, 15-30 x 0.01 lb
Operating Environment:	Temperature: 23°F-104°F (-5°C-40°C) Humidity: 20-85% (no condensation)
Display Unit:	12.1-in TFT color LCD with LED backlight SVGA (800 x 600)
Display Items:	Tare: Four-digits Unit Price: Five-digits Weight: Five-digits
Total Price:	Six-digits
Interface:	USB x 4 channel SD card x 1 channel
Memory Capacity:	2 GB
Communication:	Static TCP/IP 10/100 Base T Ethernet DHCP
Print Head:	3in (80mm) direct thermal (12 dot/mm)
Print Speed:	Up to 5.9in (150mm) per second
Label Size:	Width: 1.5-3.1 in (38-80mm) Length: 1.2-7.9 in (30-200mm)
Label Roll:	Inside Diameter: 3.0in (76mm) min. Outside Diameter: 9.0in (230mm) max.
Weight:	Main Body: 42lb (19kg) Scale Unit: 13lb (6kg)
Power Supply:	AC110 V-120 V, 50/60 Hz, 4 A
Power Consumption:	Stand-by: 50 W In operation: 120 W
Classification:	NTEP CC 06-029

Warranty

One-year limited warranty

Approvals



RICE LAKE
RETAIL SOLUTIONS

230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com/retail

An ISO 9001 registered company © 2015 Rice Lake Weighing Systems PN 173049 12/15
Specifications subject to change without notice.