



Application Note:

Combics 1 indicator is designed for use with both Combics, IF and IS series platforms. However, various accessories may differ and are application dependent.

Part Number/Price

RLWS PN	Minebea PN	Description	Est. Weight	Price
102396	CAISL1-U	IP44 protection rated	7.5 lb	Consult
102398	CAIS1-U	IP69K protection rated	7.5 lb	Consult
115668	CAISL1-UV1	IP44, controller for IS base	7.5 lb	Consult
115671	CAIS1-UV1	IP69K, controller for IS base	7.5 lb	Consult

Options/Accessories

RLWS PN	Minebea PN	Description	Price
105607	YDH02CISUS	Wall mount bracket	Consult
171727	YDH12CWSUS	Bench mount bracket	Consult
156440	YDH01CWSUS	Post mount assembly for 10 × 10 in platforms, 13 in high	Consult
156441	YDH02CWSUS	Post mount assembly for 12 × 12 in platforms, 19 in high	Consult
156442	YDH03CWSUS	Post mount assembly for 18 × 18 in platforms, 29 in high	Consult
103049	YAS02MI	24 V industrial power supply	Consult
162640	YDO02C-ETH	Ethernet TCP/IP	Consult
155826	YDO02C-AO	Analog output, 0-20 mA, 4-20 mA, 0-10 V	Consult
193049	YDC01CI	Dust cover pack of two	Consult
Cables			
155804	YCC05-001M2	RS-232 9/25-Pin D-Sub female, 1.5 m, IP44	Consult
155805	YCC01-USBM2	RS-232 to USB connector, 2 m IP44	Consult
155806	YCC02-D25F6	RS-232 open to 25 D-Sub female	Consult

Standard Features

- Amber backlit LCD display, 0.8 in
- External calibration routine
- RS-232C
- On/Off, Zero, Tare, Print/Data keys
- Function keys for: Gross/net toggle; three-way unit toggle; 10X higher resolution toggle
- Automatic tare feature
- One scale connection

Specifications

Load Cell Connection:

4 or 6 wire

Excitation Voltage:

9 V

Power Requirements:

120 to 240 VAC, 17 W / 23 VA maximum

Housing:

AISI 304 stainless steel

Dimensions:

(L × W × H)
 11.9 × 7.4 × 3.5 in
 (302.26 × 187.96 × 88.9 mm)

Operating Temperature:

14 °F to 104 °F (-10 °C to 40 °C)

IP Rating:

IP44, IP69K

Net Weight:

5 lb (2.3 kg)

Warranty:

Two-year limited
 Accessories: One-year limited

PRECISION INDUSTRIAL WEIGHING