



www.ricelake.com

WS911

SCREW WEIGHERS

By providing a screw conveyor with a weigh system, one can easily measure the bulk product flow.

Therefore the screw conveyor is mounted at the inlet in a set of special pivots and connected to a loadcell near the outlet and provided with a speed encoder.

Two flexible connections take care of a dust tight inlet and outlet.

This screw weigher is available for ATEX categories II2D and II3D (zone 21 and 22).



ASSEMBLY

Weighframe, model WS911

Construction: Fixed frame with frictionless pivots and a loadcell

carrier, mounted on or at an existing or to be realized construction. The screw conveyor will be mounted in

the loadcell carrier and the pivots.

Mounting: A construction has to be foreseen, in which the weighframe is mounted with only 6 bolts.

Material: Steel St.37 / SS304

Finishing: Powder coating, colour RAL 3020 / Shot blasting SA 2.5

Loadcell, model S-beam

Type loadcell: Tension force transducer **Construction:** Hermetically sealed, IP67

Material: SS

Junction box, model JBW

The Junction box is placed near the weighframe

Dimensions: 180 x 110 x 90 mm (l x w x h)

Material: Shockproof reinforced polycarbonate

Protection: IP66

Loadcells: 2 pieces (4- of 6-wires) **Speed pickup:** yes (2- or 3-wires)

Speed Pick-Up, model SPU 5020 / 5826

This digital speed pickup is mounted directly on the axle end

of the none driven drum.

Housing: Aluminium / SS304, IP66

Screw conveyor for screw weighing, model WSCxxx-P1M-yyyy

Material: Steel St.37 / SS304

Finish: Painting RAL 5017 / Shot blasting

Drive: SEW type R / IP54 / 230-400 VAC / 50 Hz


Bearing: Y-Bearing in flange type

Sealing: Gland Packing or Labyrinth or Air purge sealing Including: Fixation points for mounting in the weighframe WS911

Electronics

See applicable datasheet.

SCREW CONVEYOR WITH SCREW WEIGHING



SALES AND TECHNICAL ASSISTANCE



HEADQUARTERS

230 West Coleman Street Rice Lake, Wisconsin 54868 - USA Tel: (715) 234 9171 | Fax: (715) 234 6967 RICE LAKE WEIGHING SYSTEMS EUROPE B.V.
Weiland 11

NL-6666 MH Heteren - The Netherlands Tel: +31 (0) 26 472 1319 | Email: europe@ricelake.com www.ricelake.com