

# Ishida Astra II

Price Computing Scale with Printer



## Approvals



## Part Number/Price

Part #	Model	Capacity	Est. Weight	Price
185822	Astra II Bench	30 lb × 0.01 lb	25 lb	Consult
185823	Astra II Pole	30 lb × 0.01 lb	25 lb	Consult
190641	Astra II Lite software CD (available for download at <a href="http://www.ricelake.com">www.ricelake.com</a> )			N/C
190642	Astra II Lite license file (for one computer only, not transferable)			Consult

## Options/Accessories

Part #	Description	Price
47977	Produce platter (sits on top platter included with scale)	Consult
47976	Fish platter (sits on top platter included with scale)	Consult
47341	Continuous roll thermal journal paper, 64 mm W × 50 m L (for reports only)	Consult
184273*	Technical manual	Consult
184270*	Additional operating manual	Consult
184274*	Additional operation card	Consult
170916	Additional operator keysheet insert	Consult
<b>Label Stock</b>		
47732	2.36 × 1.73 in (60 × 44 mm)	Consult
47733	2.52 × 1.85 in (64 × 47 mm)	Consult
47735	2.52 × 2.32 (64 × 59 mm)	Consult
47736	Pre-printed safe handling instructions, 2.52 × 2.32 in (64 × 59 mm)	Consult
47743 ***	Extended text, 2.52 × 3.34 in (64 × 85 mm)	Consult
47745	Pre-printed safe handling instructions on top of label, 2.52 × 3.34 in (64 × 85 mm)	Consult
47753	Blank 2.52 × 1.46 in (64 × 37 mm)	Consult
47754	Blank 2.52 × 1.85 in (64 × 47 mm)	Consult
47761	Continuous strip label stock 2.25 x 121 in (64 x 37,000 mm)	Consult
47762	Non-bar code, 2.52 × 2.32 in (64 × 37 mm)	Consult
105346	Blank 2.52 × 3.34 in (64 × 85 mm)	Consult

Label stock, please consult factory for case quantity pricing. Examples shown on page 927

Labels sold by the case-12 rolls per case.

\* Manuals and software programs can be downloaded at [www.ricelake.com](http://www.ricelake.com)

\*\*\* Safe handling instructions can also be printed by scale

## Standard Features

- Programmable function keys
- Blue alphanumeric LCD display
- Convenient side-loading label feature
- Wired Ethernet
- Customer display

## Specifications

### Power:

AC 100 to 240 V, 50/60 Hz

### Power Consumption:

Standby: 50 w  
In operation: 100 w

### Resolution:

Display: 3,000 divisions

### Communication Ports:

Ethernet: TCP/IP 10/100 Base-T  
USB: data backup and restore

### Memory Capacity:

2 MB

### Annunciators:

Net, zero, save, auto

### Display:

Blue alphanumeric LCD display (23 digits, 16 segments)

### Display Items:

Tare: four-digits  
Unit price: five-digits  
Total price: six-digits

### Keys/Buttons:

84 one-touch preset keys, 168 presets (assign two items/key)

### Printing Speed:

3.9 in (100 mm) per second

### Printing:

Direct thermal 2.2 in (56 mm) (448 dot, 8 dot/mm)

### Label Size:

Width: 1.5 to 2.5 in (38 to 64 mm)  
Length: 1.2 to 6.9 in (30 to 175 mm)

### Label Roll:

Inside diameter: 1.6 in (40 mm)  
Outside diameter: 3.9 in (100 mm)

### Label Backing Paper:

Width: Up to 2.6 in (66 mm)

### Temperature Range:

Certified: 14 °F to 104 °F (-10 °C to 40 °C)

### Warranty:

One-year limited

### Approvals:

NTEP 07-005  
UL

# Ishida Astra II

Price Computing Scale with Printer

## Dimensions

<b>Bench</b>
<b>Unit</b>
17.2 × 16.1 × 6.3 in (437 × 410 × 159 mm)
<b>Stainless Steel Platter</b>
10.5 × 14.6 in (268 × 370 mm)
<b>Pole</b>
<b>Unit</b>
17.2 × 16.1 × 6.3 in (437 × 410 × 159 mm)
<b>Stainless Steel Platter</b>
10.5 × 14.6 in (268 × 370 mm)
<b>Unit with Pole</b>
19.7 × 16.1 × 20.6 in (500 × 410 × 524 mm)

