

INTRINSICALLY SAFE

# EL232 XPCD

Explosion Proof Remote Serial Display



HAZARDOUS LOCATION INSTRUMENTATION

NOTE: Custom enclosures as requested. All explosion-proof devices are now built-to-order, so please coordinate purchase of these items with one of our application specialists.

## Standard Features

- 20 mA current loop or RS-232 input
- Compatible with most Rice Lake indicators
- NEMA Type 4, 7CD, 9EFG enclosure

## Specifications

**Input Voltage:**

115 VAC, 60 Hz

**NEC Classifications:**

Class I, Division 1, Groups C & D; Class II, Division 1, Groups E, F & G and Class III hazardous environments

**Baud Rate:**

1200, 2400, 4800 and 9600

**Interfaces:**

20 mA current loop and RS-232  
Please consult factory for model numbers and interface requirements

**Display:**

High-intensity, red LED, 0.8 in (20.3 mm) high digits

**Weight:**

Approximately 60 lb (27.2 kg)

**Warranty:**

One-year limited

## Part Number/Price

Part #	Description	Est. Weight	Price
20904	EL232 XPCD explosion proof remote serial display	60 lb	Consult

## Dimensions

EL232 XPCD			
A	10.50 in (266.7 mm)	E	10.50 in (266.7 mm)
B	9.50 in (241.3 mm)	F	7.50 in (190.5 mm)
C	5.81 in (147.7 mm)	G	11.75 in (298.5 mm) (glass diameter)
D	11.75 in (298.5 mm)	H	7/16 in (11 mm) dia holes



**CAUTION!** The equipment contained within this Explosive Environment section requires greater attention to specification and installation guidelines. Improper specification, installation or service of these products can result in loss of equipment or serious injury.

