

# Ishida IP-Ai-P

Large Roll Label Printer  
with Color Touchscreen



**RICE LAKE**  
RETAIL SOLUTIONS

**ISHIDA**

800-472-6703 [www.ricelake.com/retail](http://www.ricelake.com/retail)

# Ishida IP-Ai-P

Large Roll Label Printer  
with Color Touchscreen



Convenient label loading

The IP-Ai-P prints at a speed of 4.7 inches per second and, with its unique batching capabilities, is ideal for high-volume printing applications in bakeries. Its custom graphics feature creates stunning labels with all required nutritional and ingredient information, and a fully customizable color touchscreen provides easy access to PLUs via category keys.

The IP-Ai-P features easy label roll front-loading with a nine-inch roll capacity to streamline prepackaging operations. For consistent and accurate pricing, the IP-Ai-P networks with ScaleLink Pro 5 and other third-party product management software.

## Standard Features

- Large color touchscreen with adjustable viewing angle
- Front-loading, 9 in (230 mm) label roll capacity
- Prints all legally required ingredient and nutritional information
- Stores and prints graphics for custom labels
- Ethernet communications
- Assign images to category, presets or function keys
- 21 tactile keys
- 585 MB of memory
- Linux operating system
- ScaleLink Pro 5 communications
- Compatible with third-party communication software including Invatron's PLUM® and ADC's InterScale®

## Options/Accessories

- Internal wireless communication, 802.11 b/g
- SLP-5 scale management software, including label design, data backup and remote diagnostics

## Specifications

<b>Operating Environment:</b>	<b>Temperature:</b> 23-104°F (-5-40°C) <b>Humidity:</b> 20-85% (no condensation)
<b>Display Unit:</b>	12.1 in TFT color LCD with LED backlight SVGA (800 x 600)
<b>Interface:</b>	USB x 4 channel SD card x 1 channel
<b>Memory Capacity:</b>	585 MB
<b>Communication:</b>	Static TCP/IP 10/100 Base T Ethernet
<b>Print Head:</b>	3.1 in (78 mm) direct thermal (12 dot/mm)
<b>Print Speed:</b>	4.7 in (120 mm) per second
<b>Label Size:</b>	Width: 1.5-3.1 in (38-80 mm) Length: 1.2-7.9 in (30-200 mm)
<b>Label Roll:</b>	Inside diameter: 3.0 in (76 mm) min. Outside diameter: 9.0 in (230 mm) max.
<b>Weight:</b>	Main body: 42 lb (19 kg)
<b>Power Supply:</b>	AC110V-120V, 50/60Hz, 4 A
<b>Power Consumption:</b>	Stand-by: 50W In operation: 120W
<b>Classification:</b>	UL Listed
<b>Warranty:</b>	One-year limited warranty

Your Rice Lake Weighing Systems distributor is:



230 W. Coleman St. • Rice Lake, WI 54868 • USA  
TEL: 715-234-9171 • FAX: 715-234-6967 • [www.ricelake.com/retail](http://www.ricelake.com/retail)

An ISO 9001 registered company © 2017 Rice Lake Weighing Systems PN 182907 4/17  
Specifications subject to change without notice.