

Ready-n-Weigh Bench Scale Package

CW-90B SCALE BASE AND
482/482 LEGEND® PLUS INDICATOR



RICE LAKE[®]
WEIGHING SYSTEMS

800-472-6703

www.ricelake.com

Ready-n-Weigh Bench Scale Package

CW-90B SCALE BASE AND 482/482 LEGEND® PLUS INDICATOR



1 INDICATOR

482 Legend or 482 Legend Plus with numeric keypad
Enclosure is NEMA Type 4X/IP66, heavy-gauge stainless steel
LCD display

2 SCALE BUILD

12-inch column
Removable top cover for easy cleaning
Rubber feet for exceptional traction while avoiding scratches

3 LOAD CELL

IP67 aluminum environmentally sealed load cell

The CW-90B Ready-n-Weigh bench scale system is a complete bench scale, column and indicator package. Pair the CW-90B IP67 rated platform with the 482 Legend indicator or choose the 482 Legend Plus for a full numeric keypad. This package is also offered with an internal battery, making it perfect for applications that require a portable bench scale.

| Capacity | Base Size |
|-----------------------------------|-------------------|
| 5 lb x 0.001lb/2.5 kg x 0.0005 kg | 10 x 10 x 4.25 in |
| 10 lb x 0.002 lb/5 kg x 0.001kg | 10 x 10 x 4.25 in |
| 25 lb x 0.005 lb/10 kg x 0.002 kg | 10 x 10 x 4.25 in |
| 25 lb x 0.005 lb/10 kg x 0.002 kg | 12 x 12 x 4.25 in |
| 50 lb x 0.01lb/25 kg x 0.005 kg | 12 x 12 x 4.25 in |
| 100 lb x 0.02 lb/50 kg x 0.01kg | 12 x 12 x 4.25 in |

STANDARD FEATURES

- Package includes scale with IP67 aluminum environmentally sealed load cell with an indicator and 12-inch column
- Factory calibrated, with indicator setup and configured for 5,000 divisions
- Scale includes rubber feet to provide exceptional traction and avoid scratching surfaces along with removable top cover for ease of cleaning
- LCD, 0.8in six-digit, seven-segment backlight display
- Battery backed time and date
- Two independent serial ports, RS-232 and 20mA for connecting to a variety of peripherals

CW-90B SPECIFICATIONS

| | |
|--------------------------------|---------------------------------------|
| LOAD CELL, NTEP CERTIFIED: | IP67 aluminum, environmentally sealed |
| SCALE CONSTRUCTION: | 304 stainless steel |
| MAXIMUM OVERLOAD: | 180 to 200% depending on capacity |
| OVERLOAD PROTECTION: | Five-point, independently adjusted |
| CABLE LENGTH: | 34 in |
| COMPENSATED TEMPERATURE RANGE: | 14° F to 104° F (-10° C to 40° C) |
| WARRANTY: | Two-year limited |

APPROVALS:



482/482 LEGEND PLUS SPECIFICATIONS

| | |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| POWER: | Line voltages: 110 - 240 VAC Frequency: 50 or 60 Hz |
| DISPLAY: | 0.8 in (20 mm), LCD, 6-digit, 7-segment display |
| INTERNAL BATTERY: | Rechargeable Lithium-Ion |
| ESTIMATED BATTERY LIFE: | 40 hours (350W load without backlight), 15 hours (350W load with backlight) |
| APPROX. CHARGE TIME: | 16 hours to achieve 100% |
| KEYS/BUTTONS: | 482 Plus Power, Gross/Net, Menu, Unit, Tare, Print, Zero and numeric keypad 482 Power, Gross/Net, Menu, Unit, Tare, Print, Zero |
| RATING/MATERIAL: | Enclosure: NEMA Type 4X/IP66, stainless steel, washdown |
| WARRANTY: | Two-year limited |

APPROVALS



SALES AND TECHNICAL ASSISTANCE

RICE LAKE®
WEIGHING SYSTEMS

HEADQUARTERS
230 West Coleman Street
Rice Lake, Wisconsin 54868 - USA
Tel: (715) 234 9171 | Fax: (715) 234 6967
www.ricelake.com