

Specifications

Scale Unit

Capacity/Division:

0-15 lb \times 0.005 lb / 15-30 lb \times 0.01 lb (Multi-interval) 0-30 lb \times 0.01 lb (Single range) 0-6 kg \times 0.002 kg / 6-15 kg \times 0.005 kg (Multi-interval) 0-15 kg \times 0.005 kg (Single range)

Scale Platter Size:

Hanging: 15 in (382) dia.

Display

Size:

Operator Side: 10.1 in; Customer Side: 7 in

Systems:

Capacitive touch Panel

Printer

Media Type:

Die-cut label; Continuous label/ Linerless label/Receipt (Optional)

Media Size:

Outside Diameter of roll: Max. 100 mm (4.0 in) or less Inner core diameter: 40 mm +/-1 mm (1.6 in) Width: 30-64 mm (linerless label: 60 mm) Length: 30-200 mm (linerless label: 30-175 mm)

Cassette:

Non-cassette (Virtual cassette function)

Thermal Head:

2.2 in (56 mm)

Resolution:

8 dot/mm (200 dpi)

Speed of Printing:

MAX: 120 mm/sec

Printing Width: MAX: 56 mm

Printing Length:

MAX: 200 mm

IVIAN. 200 IIIIII

Bar Code Type: JAN, EAN, EAN128, CODE128, UPC, ITF. GS1. QR Code

Control

I/O Port:

TCP/IP, USB, RS-485, Connector for external scale

OS:

Linux

Communication:

Ethernet, wireless

Approvals:

NTEP CC 23-036 cULus



Ishida Uni-8H

Price Computing Scale/Printer/Color Touchscreen

Standard Features

- Large color touchscreen (10 in)
- Adjustable touchscreen viewing angle
- Play videos with sound on customer and operator display
- 10 in (800×600) operator display 7 in (800×480) customer display
- Dual-range weighing (0 to 15 lb \times 0.005 lb, 15 to 30 lb \times 0.01 lb)
- Label printing: die-cut labels and/or continuous paper
- Customizable label formats: 999
- · PC-based scale operating system
- · Solid state drive eliminates moving parts
- SSD memory 250 MB

- SD memory card slot
- Up to 120 mm/sec print speed
- 2020 nutrition labeling
- Fully compliant with RoHS regulations for a completely lead-free machine
- Barcodes: EAN/UPC 8/12/13, ITF FS1, QR CODE, GS1, CODE128 and EAN128
- Compatible with many third-party software communication packages
- Remote access
- · Control for 3rd party driver

Options

- ScaleLink Pro 5 scale management software, including label design, data back-up and remote diagnostics
- Seafood/Produce platter

PART #	MODEL	WIRELESS	CAPACITY
220032	Uni-8 Hanging	V	0 to 15 × 0.005 lb / 15 to 30 × 0.01 lb





Label Replacement Training

Ishida Uni-8H

Price Computing Scale/Printer/Color Touchscreen

PART #	MODEL/DESCRIPTION	WIRELESS	CAPACITY	EST. SHIP WEIGHT	PRICE
220032	Uni-8 Hanging	$\sqrt{}$	0 to 15 × 0.005 lb / 15 to 30 × 0.01 lb	31 lb	Consult

Options/Accessories

Communication

152628*	ScaleLink Pro 5 license file, one license required per computer (version 2.62 or higher required)	Consult
78860	Cross cable, Ethernet CAT5, 6ft	Consult


Manuals and Service Tools


118188**	Uni Series support USB (contains manuals, training videos and libraries)	
160906	USB flash memory, 1 GB	
222152**	User manual	Consult
222153**	Service manual	Consult
Consult**	Installation manual	Consult

Label Stock

Please refer to labels section of this catalog for ordering information and case quantity pricing

DIMENSIONS HANGING				
A	1.8 in (45 mm)	Е	8.2 in (207 mm)	
В	1.8 in (45 mm)	F	15.0 in (382 mm)	
С	28.3 in (719 mm)			
D	14.6in(370 mm)			





^{*}Software key is provided after online registration is completed

^{**}Manuals and software programs can be downloaded from the distributor section of www.ricelake.com/retail