

# TagMaster CT-45

Network IP Camera with License Plate Recognition (LPR)



## Standard Features

- Compatible with OnTrak® Enterprise
- Plate localization, country and state identifiers
- Optical Character Recognition (OCR) Library
- Number and letter segmentation
- Works in daylight and low-light conditions
- Operating range, 10 to 82 ft (3 to 25 m)

## Specifications

**Read Range:**  
10 to 82 ft (3 to 25 m)

**Image Sensor:**  
2 megapixels  
1/2.8 in CMOS sensor

**Frame Rate:**  
25 FPS

**Interface:**  
LAN (weatherproof standard RJ-45) 10/100 Mbps  
Ethernet interface Wi-Fi (for easy setup)  
Relay Control (1 input, 2 outputs) Wiegand

## Specifications Continued

**Power Input/Network:**  
24 to 48 VDC, PoE+ IEEE 802.3 at  
Requires CAT 5e or better network, POE+ network  
switch or 24-48 VDC power supply

**Power Consumption:**  
Average 18W, max 25W

**Dimensions:**  
4.0 × 7.0 × 11.5 in  
(102 × 180 × 290 mm)

**Weight:**  
6.5 lb (2.95 kg)

**Rating:**  
IP66

**Operating Temperature:**  
-40 °F to 140 °F (-40 °C to +60 °C) 0% to 95% RH

**Approvals:**  
IEC 62368-1, Electrical Safety General  
IEC 60950-22, Electrical Safety Outdoor  
IEC 62471, Photobiological  
EN 55022:2010, Emissions  
EN 55024:2010, Immunity  
IEC 60068-2-27 Ea, Shock  
IEC 60068-2-64 Fh, Vibration  
UL94 HB, Flammability  
RoHS directive 2002/95/EC and RoHS2 directive  
2011/65/EU

## Part Number/Price

Part #	Description	Price
220688	Camera LPR	Consult
220690	Mounting bracket, LPR camera	Consult
220691	Cable power & relay LPR camera power cable	Consult

AUTOMATED  
TICKETING

# Vivotek IP8361

Network IP Outdoor Camera



## Standard Features

- Compatible with OnTrak® Enterprise
- Includes motion detection
- Remotely pan and tilt camera horizontally and vertically
- IR night vision makes images clear even in the dark
- Operating range, 10 to 82 ft (3 to 25 m)

## Specifications

**Read Range:**  
10 to 82 ft (3 to 25 m)

**Interface:**  
10Base-T/100 Base TX Ethernet (RJ-45)

**Power Input:**  
IEEE 802.3af PoE Class 3

**Power Consumption:**  
Max. 7.2 W (PoE)

**Dimensions:**  
3.3 × 8.3 in  
(83 × 212 mm)

**Operating Temperature:**  
-4 °F to 122 °F  
(-20 °C to 50 °C)

**Weight (including bracket):**  
3.5 lb (1.6 kg)

**Rating:**  
IP66

**Approvals:**  
CE  
LVD  
FCC Class A  
VCCI  
C-Tick

## Part Number/Price

Part #	Description	Price
163175	Ethernet camera 2-megapixel CMOS sensor	Consult
131605	Power supply, POE injector	Consult
15438	Power cord	Consult