

Datalogic PowerScan® PD9130 Series

Linear Imager Handheld Scanner



SCANNERS

Standard Features

- Durable—tested to 50 drops of 2 m / 6.6 ft
- 25 kV electrostatic protection
- Datalogic's patented 'Green Spot' technology for good-read feedback
- Aladdin® software for configuration
- Linear Imager

Specifications

Light Source:

Aiming 630 to 680 mm VLD

Decode Capabilities:

GS1 DataBar™ linear codes, UPC/EAN, UPC/EAN P2/P5 add ons, UPC/EAN Coupons, ISBN, Code 128, EAN 128, Code 39, Code 39 Full ASCII, Code 39 CIP, Code 32, Codabar, Interleaved 2 of 5, IATA, Industrial 2 of 5, Standard 2 of 5, Code 11, MSI, Plessey, Code 93, Follet 2/5, Code 4, Code 5, Datalogic 2 of 5, Codablock F

Dimensions:

(L × W × H)
8.0 × 3.0 × 4.5 in
(20.3 × 7.6 × 11.4 cm)

Display:

LED

Weight:

280.0 g (9.9 oz)

Communications:

Keyboard wedge, USB or RS-232

Operating Temperature:

-22 °F to 122 °F (-30 °C to 50 °C)

Storage Temperature:

-22 °F to 122 °F (-30 °C to 50 °C)

Humidity:

5% to 95% non-condensing

IP Rating:

IP65

Drop Resistance:

6.6 ft (2 m)

Warranty:

Three-year limited

Part Number/Price

Part #	Description	Weight	Price
195144	Scanner, PD9130 YB multi-interface, requires cable - (ordered separately)	4 lb	Consult
195145	Scanner kit, PD9130 YBK2 scanner and RS-232 cable - (included)	4 lb	Consult

Options/Accessories

Part #	Description	Price
195146	Kit, universal mount, Datalogic STD-P090	Consult
108217	RS-232 cable, CAB-434, 8 ft, nine-pin female coiled, PD9100 Series	Consult
195147	USB cable, CAB-524 for use with PD9130 only	Consult
108219	Keyboard wedge cable, CAB-437, PD9100 Series	Consult
192322	Power supply, desktop 5 volt, 12 W, PD9100 Series	Consult
41276	DB9-M Pin blunt end cable	Consult
Consult	RS-232 coiled 12 ft, CAB 467	Consult
Consult	RS-232 coiled 15 ft, CAB 486	Consult
Consult	USB, 8-0734-08	Consult