


# Summit® 3000 Low-Profile Floor Scale

FLOOR SCALES



## APPROVALS



Measurement  
Canada  
Approved



The load cell cable exits weldment toward the interior of scale, allowing flexibility to route it out any side of scale to digital weight indicator.

## STANDARD FEATURES

- Four NTEP Certified alloy steel shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- Four adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–13NC) located in center of the deck for easy lifting
- 20 ft of EL147 load cell cable
- Two-year limited warranty

## SPECIFICATIONS

### End Load Capacity:

100% full scale at 2,000 lb and 5,000 lb  
80% full scale at 10,000 lb

### Cable Length:

20 ft (6.1 m) (for connecting junction box to indicator)

### Approvals:

NTEP CC 03-014, Class III 5,000d  
Measurement Canada AM-5530, Class III 5,000d

### Warranty:

Two-year limited warranty

## PART NUMBER/PRICE

PART #	SIZE (W X L X H)*	CAPACITY	EST. SHIP WEIGHT	PRICE
<b>Single Scale</b>				
74715	3 ft x 3 ft x 3.625 in	2,000 lb	190 lb	Consult
74716	4 ft x 4 ft x 3.625 in	2,000 lb	305 lb	Consult
74717	4 ft x 4 ft x 3.625 in	5,000 lb	305 lb	Consult
74718	4 ft x 4 ft x 3.625 in	10,000 lb	305 lb	Consult
74719	4 ft x 5 ft x 3.625 in	5,000 lb	395 lb	Consult
74720	4 ft x 5v x 3.625 in	10,000 lb	445 lb	Consult
74721	4 ft x 6 ft x 3.625 in	5,000 lb	470 lb	Consult
74722	4 ft x 6 ft x 3.625 in	10,000 lb	525 lb	Consult
74723	5 ft x 5 ft x 3.625 in	5,000 lb	505 lb	Consult
74724	5 ft x 5 ft x 3.625 in	10,000 lb	575 lb	Consult
<b>Single Scale—Canadian Weights and Measures Certified</b>				
77440	3 ft x 3 ft x 3.625 in	1,000 kg	190 lb	Consult
77373	4 ft x 4 ft x 3.625 in	1,000 kg	305 lb	Consult
77346	4 ft x 4 ft x 3.625 in	2,500 kg	305 lb	Consult
77347	4 ft x 4 ft x 3.625 in	5,000 kg	305 lb	Consult
82880	4 ft x 5 ft x 3.625 in	2,500 kg	395 lb	Consult
82881	4 ft x 5 ft x 3.625 in	5,000 kg	445 lb	Consult
77348	5 ft x 5 ft x 3.625 in	2,500 kg	505 lb	Consult
77349	5 ft x 5 ft x 3.625 in	5,000 kg	575 lb	Consult
<b>5-Scale Package</b>				
75809	3 ft x 3 ft x 3.625 in	2,000 lb	850 lb	Consult
75810	4 ft x 4 ft x 3.625 in	2,000 lb	1,400 lb	Consult
75811	4 ft x 4 ft x 3.625 in	5,000 lb	1,400 lb	Consult
75812	4 ft x 4 ft x 3.625 in	10,000 lb	1,400 lb	Consult
75813	4 ft x 5 ft x 3.625 in	5,000 lb	1,870 lb	Consult
75814	4 ft x 5 ft x 3.625 in	10,000 lb	2,115 lb	Consult
75815	4 ft x 6 ft x 3.625 in	5,000 lb	2,210 lb	Consult
75816	4 ft x 6 ft x 3.625 in	10,000 lb	2,495 lb	Consult
75817	5 ft x 5 ft x 3.625 in	5,000 lb	2,325 lb	Consult
75818	5 ft x 5 ft x 3.625 in	10,000 lb	2,675 lb	Consult
<b>5-Scale—Canadian Weights and Measures Certified</b>				
77472	3 ft x 3 ft x 3.625 in	1,000 kg	850 lb	Consult
77473	4 ft x 4 ft x 3.625 in	1,000 kg	1,400 lb	Consult
77474	4 ft x 4 ft x 3.625 in	2,500 kg	1,400 lb	Consult
77475	4 ft x 4 ft x 3.625 in	5,000 kg	1,400 lb	Consult
82885	4 ft x 5 ft x 3.625 in	2,500 kg	1,870 lb	Consult
82886	4 ft x 5 ft x 3.625 in	5,000 kg	2,115 lb	Consult
77476	5 ft x 5 ft x 3.625 in	2,500 kg	2,325 lb	Consult
77477	5 ft x 5 ft x 3.625 in	5,000 kg	2,675 lb	Consult

**Summit® 3000** Low-Profile Floor Scale**OPTIONS/ACCESSORIES**

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
75819	Floor anchor plates, mild steel (set of two)		Consult
N/A	Top access foot adjust holes		Consult
76012	Additional operating manual		Consult
<b>Access Ramps</b>			
74953***	3 ft x 3 ft x 3.625 in	133 lb	Consult
74954***	4 ft x 3 ft x 3.625 in	177 lb	Consult
74955***	5 ft x 3 ft x 3.625 in	226 lb	Consult
74956	3 ft x 4 ft x 3.625 in	177 lb	Consult
74957	4 ft x 4 ft x 3.625 in	224 lb	Consult
74958	5 ft x 4 ft x 3.625 in	272 lb	Consult
<b>Pit Frames</b>			
75036	3 ft x 3 ft	100 lb	Consult
75037	4 ft x 4 ft	125 lb	Consult
75040	5 ft x 5 ft	155 lb	Consult
75038	4 ft x 5 ft	140 lb	Consult
75039	4 ft x 6 ft	157 lb	Consult

\* For custom sizes or capacities please consult factory for RoughDeck® HP pricing

\*\* For use with DC-190 counting scales \*\*\*Not recommended for use with pallet jacks