

Datalogic PowerScan® RF 8000 Series



STANDARD FEATURES

- IP65 rating
- Wireless operation
- Operates up to 10 hours on a single charge
- Scanner and base station are IP64
- Green spot - good read feedback
- Polycarbonate molded with rubber
- Multi-point operation allows for multiple scanner communications to a single base station

Note: Fork-lift conversion kit available special order 18-36V or 48-72V

SPECIFICATIONS

DIMENSIONS:

Scanner: 8.4in x 4.5in x 2.8in
(212mm x 109mm x 71mm)
Base Station: 10.5in x 3.5in x 2.5in
(266.7mm x 88.9mm x 63.5mm)
(width is 4.2in/106.68mm including mounting knobs.)

WEIGHT:

Scanner: 13.9oz (395g)
Base Station: 16oz (454g)

DISPLAY:

LCD: 4 lines x 16 characters

LIGHT SOURCE:

VLD between 630-380nm

BASE STATION:

US: 110V±10%, 60Hz

COMMUNICATIONS:

Host: RS232 with DB9 S, P/S and 12ft cable.
KBW (keyboard wedge) with P/S and 6M Din, coiled cable 12ft.
USB, 12ft coiled cable
Frequency range:
(varies by country) 915mHz

OPERATING TEMPERATURE:

-4°F to 122°F (-20°C to 50°C)

STORAGE TEMPERATURE:

-4°F - 158°F (-20°C to 70°C)

HUMIDITY:

90% non-condensing

DROP RESISTANCE:

2m

BATTERY TYPE:

2150 Li-Ion battery pack

ELECTRICAL:

Complies to C-CSA-US
(60950 Canada and USA)

PART#	DESCRIPTION	EST. SHIP WEIGHT	PRICE
104967.....	PowerScan RF Scanner with battery, SR, 915MHz for RS-232/ keyboard wedge/wand emulation interfaces.....	4 lb	Consult factory

OPTIONS/ACCESSORIES

104968.....	PowerScan RF Base Station, 915MHz for RS-232/ keyboard wedge/wand ...	5 lb	Consult factory
82281.....	PowerScan Quick Scan US, AC power adapter	3 lb	Consult factory
104969.....	Cable, Wedge, Y, 6-pin mini DIN, 5-pin D/N, universal adapter cable		Consult factory
108217.....	Cable, RS-232, 9-pin D-sub, 12ft.....		Consult factory