

# Crane/Hanging Scales

## Intercomp CS™ 200

Crane Scale




APPROVALS



### STANDARD FEATURES

- Lightweight and compact
- Digital calibration
- Auto shut-off
- lb/kg selectable
- Peak hold feature



### SPECIFICATIONS

**RESOLUTION:**

12 bit A/D delivers more than 1 million internal counts

**CONTROLS:**

Zero, lb/kg, on/off

**DISPLAY:**

0.5 in (12 mm) 5-digit LCD

**POWER:**

One 9V disposable alkaline dry cell (or rechargeable nickel-cadmium cell, not included) Battery life is one year of normal use.

**DIMENSIONS: (W x D x H)**

3.75 in W x 2 in D x 6 in H  
(94 mm W x 50 mm D x 150 mm H)

**ENCLOSURE:**

Weatherproof ABS plastic case

**APPROVALS:**

CE

**AUTO SHUT-OFF:**

Low battery, or after 5 minutes without use

**ACCURACY:**

±0.1% of applied load

**TEMPERATURE:**

Operating -4°F to 140°F  
(-20°C to 60°C)

**NOMINAL OVERLOAD:**

200% of capacity

**MAXIMUM OVERLOAD:**

500% of capacity

**WARRANTY:**

One-year limited warranty

**PART # DESCRIPTION**

**CS200 (battery included):**

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
43734	CS200, 25 lb (12.5 kg) x 0.01 lb (0.01 kg)	2 lb	Consult factory
43735	CS200, 50 lb (25 kg) x 0.02 lb (0.01 kg)	2 lb	Consult factory
43736	CS200, 100 lb (50 kg) x 0.05 lb (0.02 kg)	2 lb	Consult factory
43737	CS200, 250 lb (125 kg) x 0.1 lb (0.05 kg)	2 lb	Consult factory
82444	CS200, 500 lb (250 kg) x 0.2 lb (0.1 kg)	2 lb	Consult factory

Crane/Hanging Scales