

CB-2 Concrete Batch Controller Multi-Scale Automated Batching System



STANDARD FEATURES

- One aggregate and one cement scale sampling 120 times per second
- Standard manual override controls
- Batch tickets with configurable field printing
- 1 megabyte database
- Material usage by day/week/month/year and inventory on hand with reporting
- Automatic aeration control for cement silos and weigh hoppers
- Multiple freefall values per material with "learning" abilities
- Split batching for loads larger than plant capacity with pre-weighing next batch for maximum throughput
- Automatic dust collection outputs
- Simulation mode for demonstration and/or testing

SPECIFICATIONS

MATERIALS:

Eight single speed aggregates
Four dual speed cements
Hot & cold metered or weighed water delivered in two additions
Six metered admixtures configurable as bottle or direct feed injected with either water addition

1 MEGABYTE DATABASE:

2200 mix designs
750 customers
200 trucks
99 materials
100 orders

STATE MODES:

CALTRAN
NYS DOT
MnDOT

LINE VOLTAGES:

115 or 230 VAC

FREQUENCY:

50 or 60 Hz

POWER CONSUMPTION:

340 mA, maximum @ 115 VAC (26 W)
240 mA @ 230 VAC (26 W)

FUSING:

115 VAC: 2 x 400 mA TR5 subminiature fuses Wickman Time-Lag 19374 Series. UL Listed, CSA certified and approved
230 VAC/North American: 2 x 315 mA TR5 subminiature fuses Wickman Time-Lag 19372 Series. UL Listed, Semco and VD Approved

FULL SCALE INPUT SIGNAL:

Up to 70 mV

EXCITATION VOLTAGE:

10 ± 0.5 VDC, 16 x 350 Ω or 32 x 700 Ω load cells per A/D card

SENSE AMPLIFIER:

Differential amplifier with 4 and 6 wire sensing

ANALOG SIGNAL INPUT RANGE:

-10 mV to +70 mV

ANALOG SIGNAL SENSITIVITY:

0.3 μV/graduation minimum @ 7.5 Hz
1.0 μV/graduation typical @ 120 Hz
4.0 μV/graduation typical @ 960 Hz

A/D SAMPLE RATE:

7.5 to 960 Hz, software selectable (120 recommended)

INPUT IMPEDANCE:

>35 M typical

INTERNAL RESOLUTION:

8 million counts/8 million 23 bit

WEIGHT DISPLAY RESOLUTION:

9,999,999

INPUT SENSITIVITY:

10 nV per internal count

SYSTEM LINEARITY:

±0.01% full scale

ZERO STABILITY:

±150 nV/°C, maximum

SPAN STABILITY:

±3.5 ppm/°C, maximum

CALIBRATION METHOD:

Software, contents stored in flash memory

INPUT VOLTAGE DIFFERENTIAL:

±800 mV referenced to earth ground

INPUT OVERLOAD:

Load cell signal lines ±10 V continuous, ESD protected

RFI/EMI PROTECTION:

Signal, excitation and sense lines protected

ANALOG OUTPUT:

Option card: 16 bit resolution DAC
Load resistance: 1.1 KΩ minimum
Voltage output: 0 – 10 VDC
Current output: 0 – 20 mA
External loop resistance: 840 Ω maximum

MICROCOMPUTER:

Motorola ColdFire® MCF5307 main processor @ 90 MHz

DIGITAL I/O:

Four I/O channels on CPU board; optional 24-channel I/O expansion boards available

DIGITAL FILTER:

Software selectable: 1–256, enhanced RATTLE-TRAP® hybrid digital filtering

SERIAL PORTS:

Four ports on CPU board support up to 115,200 bps; optional dual-channel serial expansion boards available

Port 1: Full duplex RS-232

Port 2: RS-232 with CTS/RTS; PS/2 keyboard interface via DB-9 connector

Port 3: Full duplex RS-232, 20 mA output

Port 4: Full duplex RS-232, 2-wire RS-485, 20 mA output

DISPLAY:

4.6 in W x 3.4 in H (116 W x 86 mm H), 320 x 240 pixel VGA Liquid Crystal Display (LCD) module with adjustable contrast, 75 Hz scan rate 26,000 cd/m² brightness

KEYBOARD:

27-key membrane panel, PS/2 port for external keyboard connection

OPTIONAL FEATURES:

Four dual or eight single speed aggregates

Four dual or eight single speed cements

Weighted water with water reservoir

Four or eight auxiliary manual controls

Dual moisture probe interface (supports 4–20 mA or 0–10 V probes)

Continuous batching with mixer controls for central mix block or precast plants

Coldfire is a registered trademark of Motorola Inc.

*Factory field installation required, minimum three days on site