

NEW

NTEP Certified
2 lb Resolution



Approvals



Part Number/Price

Part #	Capacity	Description	Est. Weight	Price
Class II, CLS-680, NTEP Certified				
231802	5000 × 2 lbs	CLS680-3436-PRO, 16 × 36 in carriage plate, 9 to 36 VDC, wired	470 lbs	Consult
231803	5000 × 2 lbs	CLS680-3436-PRO, 16 × 36 in carriage plate, 9 to 36 VDC, cableless	485 lbs	Consult
Class II, CLS-920i, NTEP Certified				
231812	5000 × 2 lbs	CLS920-3436-PRO, 16 × 36 in carriage plate, 9 to 36 VDC, wired	480 lbs	Consult
231813	5000 × 2 lbs	CLS920-3436-PRO, 16 × 36 in carriage plate, 9 to 36 VDC, cableless	495 lbs	Consult
Class II, VIRTUi³ M Series, NTEP Certified				
231816**	5000 × 2 lbs	CLSM-3436-PRO, 16 × 36 in carriage plate, wired with DB9 adapter	455 lbs	Consult

**Weight indication device (PC/tablet) is not included, consult factory to verify compatibility with your device.
For indicator drawings and dimensions, please see page 410 and page 411
For scale drawings and dimensions, visit www.ricelake.com.

Standard Features

- NTEP Certified
 - 5,000 × 2 lb capacity and resolution, up to 42-in forks
 - Two 5,000-lb stainless steel load cells
 - iQUBE series digital junction box, stainless steel enclosure
- Large viewing window for operator
- 1.5-in thick steel front and rear plates
- Top cleats are pinned, bolted and welded
- Four flexure system made from high strength stainless steel
- Debris guards for top and sides
- Stainless steel load cell rod bolts
- Replaceable centering pin
- Replaceable centering notch
- Overload and underload stops
- Field serviceable flexures and load cells
- Wired or cable-less connectivity

Weight Indication Choices

- CLS-680
- CLS-920i
- Windows® Mobile PC, Tablets and handhelds, compatible with VIRTUi³

Presale Requirements

- Provide completed forklift questionnaire for quotation
- Compatible with most Class II forklift attachments, consult factory

Installation Recommendations

- When installing a forklift scale, OSHA requires the end user to de-rate the lift capacity of the forklift

Options

- Narrow width backplate
- Front plate width variations
- CLS-680, 18 to 72 VDC
- Mobile printer

Specifications

Warranty:

Two-year limited

Approvals:

NTEP 06-074



FORKLIFT /
PALLET JACK SCALES