

FIELDBUS CARDS

DeviceNet® Interface

880™/882D/882IS/1280™



Standard Features

- DeviceNet communication adapter
- 125 Kbps, 150 Kbps and 500 Kbps baud rate
- Onboard diagnostic LEDs

Specifications

Power:

3.3 VDC, 250 mA

Connector Type:

Pluggable screw terminal

IP Address Range:

MAC ID 0 to 63

Diagnostic LEDs:

Module status and network status

Dimensions:

2.00 × 1.90 × 0.75 in
(52 × 49 × 19 mm)

Temperature:

Operating:
-40 °F to 158 °F (-40 °C to 70 °C)

Part Number/Price

Part #	Description	Est. Weight	Price
179162	DeviceNet interface kit for 880 indicator	1 lb	Consult
165793	DeviceNet interface kit for 1280 indicator	1 lb	Consult
190531	DeviceNet interface kit for 882D and 882IS indicators	1 lb	Consult

NOTE: Kit includes module and carrier board

Options/Accessories

Part #	Description	Price
156783	Additional operating manual	Consult

INDICATORS /
CONTROLLERS

Modbus TCP Interface

880™/882D/882IS/1280™



Standard Features

- Active module with serial and parallel application interface
- Complete Modbus TCP server
- Up to eight bytes of I/O data
- Transformer isolated interface 100 Mbps full duplex Ethernet
- Onboard diagnostic LEDs
- CE and UL compliant

Specifications

Power Requirements:

3.3 VDC, 250 mA

Connector Type:

RJ-45

Diagnostic LEDs:

Link status, network status, module status

Dimensions:

2.00 × 1.90 × 0.75 in
(51 × 48 × 19 mm)

Temperature:

Operating: -40 °F to 176 °F (-40 °C to 85 °C)

Part Number/Price

Part #	Description	Est. Weight	Price
179161	Modbus TCP Interface kit for 880 indicator (single port)	1 lb	Consult
205568	Modbus TCP Interface kit for 880 indicator (dual port)	1 lb	Consult
165796	Modbus TCP Interface kit for 1280 indicator (single port)	1 lb	Consult
190533	Modbus TCP Interface kit for 882D and 882IS indicators	1 lb	Consult

NOTE: Kit includes module and carrier board

Options/Accessories

Part #	Description	Price
156782	Additional operating manual	Consult