

RL Web Display

Remote Scale Monitoring Software



Part Number/Price

Part #	Description	Price
219392	Software, RL Web Display remote display software	Consult

Options/Accessories

Part #	Description	Price
Consult	Non-Rice Lake indicator interface (Customer must supply technical manual with indicator for creation of driver)	Consult

Standard Features

- Replicates weight display for one or more indicators
- View live data remotely
- Multiple users can have a licensed installation
- ZERO key and Stop/Go commands function remotely

System Requirements

- Windows 10® build 1607 or newer (64 bit only) or equivalent Windows® Server OS
- 2.0 GHz processor or faster
- 250 MB drive space needed for install
- 8 GB ram or greater
- Ethernet TCP/IP connection
- A supported web browser (Google® Chrome®, Microsoft® Edge®, Mozilla® Firefox® or Apple® Safari®)

NOTE: Indicators and remote displays must be connected via Ethernet TCP/IP.

Compatible Instrumentation

- 1280 Enterprise™ Series
- 920i® Series
- 880/880 Plus Performance™ Series
- 820i™ Series
- 720i™ Series
- VIRTUi2® PC-based HMI for iQUBE2®
- 682 Synergy Series
- 680 Synergy Series
- SCT-2200 Advanced Series
- 480 Legend™ Series
- 420 Plus
- IQ Plus® 355
- IQ Plus® 710
- Avery Weigh-Tronix® E1105
- Avery Weigh-Tronix® W1127
- Mettler Toledo® 8530
- Cardinal® 738
- LaserLight2™ and LaserLight3™ in legacy mode

NOTE: Custom drivers available on request