

Due to the variety of configurations, please consult the factory to discuss application requirements and for complete specifications and price quotations.

Approvals



Package includes: Factory-

assembled scale module(s) including weighbridge, deck, lever system installed in scale frame; inboard transverse lever (for electronic conversion) is supplied standard unless outboard transverse lever is specified at time of order; manhole access provided through scale deck.

Package does not include:

Foundation steel; approach coping angle; home run cable; concrete; indicator; printer; freight charges including material handling, shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.

Standard Features

- Above-ground or in-pit foundation
- Factory-assembled, self-contained modules
- Individual module lengths from 10 ft to 40 ft
- Multiple modules create desired scale length
- Standard levers: 32.5 ton sectional rating
- Standard height: 30 in
- NTEP Certified 05-018
- Standard deck: 3/8 in thick diamond safety treadplate
- Standard widths from 10 ft to 14 ft
- Capacities to 400,000 lb

Options

- Side pipe rails
- Steel bulkheads
- Conversion s-beam load cell(s)
- Load cell mounting hardware
- Indicator
- Printer
- · Other peripheral equipment

Specifications

Full Scale Capacity:

Standard 60,000 to 200,000 lb Custom up to 400,000 lb

Concentrated Load Capacity (CLC): Standard 50,000 to 70,000 lb Custom up to 100,000 lb

Approvals:

NTEP Certified 05-018 per H-44, Class IIIL Measurement Canada AM-5598

Warranty:

Weighbridge: Two-year Pivots, bearings, suspension and mounting parts of the corner assemblies: One-year



SURVIVOR® ATV-M

Self-Contained Levertronic, Steel Deck

Length/Capacity

| Length | Capacity | Est. Weight | Number of Modules | Lever Sections | Section Capacity | Part # | Model | Price |
|----------|------------------|---------------------|-------------------------|-------------------|---------------------|--------|---------------|---------|
| SURVIVOR | ATV-M - Steel De | eck - 10 Foot Width | | | | | | |
| 30 ft | 50 tons | 16,600 lb | 1 | 2 | 35 tons | 90074 | 530C10-S | Consult |
| 35 ft | 75 tons | 20,000 lb | 1 | 3 | 35 tons | 90076 | 735C10-S | Consult |
| 40 ft | 75 tons | 22,300 lb | 1 | 3 | 35 tons | 90123 | 740C10-S | Consult |
| 50 ft | 100 tons | 28,500 lb | (2)-25 ft | 4 | 35 tons | 90125 | 1050C10-S | Consult |
| 60 ft | 100 tons | 33,750 lb | (2)-30 ft | 4 | 35 tons | 90129 | 1060C10-S | Consult |
| 70 ft | 100 tons | 39,500 lb | (1)-30 ft (1)-40 ft | 5 | 30 tons | 90135 | (A) 1070C10-S | Consult |
| 70 ft | 100 tons | 40,500 lb | (2)-35 ft | 6 | 35 tons | 90136 | (B) 1070C10-S | Consult |
| 80 ft | 100 tons | 45,100 lb | (2)-40 ft | 6 | 35 tons | 90142 | 1080C10-S | Consult |
| SURVIVOR | ATV-M - Steel De | ck - 11 Foot Width | | | | | | |
| 30 ft | 50 tons | 17,700 lb | 1 | 2 | 35 tons | 90070 | 530C11-S | Consult |
| 35 ft | 75 tons | 21,300 lb | 1 | 3 | 35 tons | 90075 | 735C11-S | Consult |
| 40 ft | 75 tons | 23,800 lb | 1 | 3 | 35 tons | 90122 | 740C11-S | Consult |
| 50 ft | 100 tons | 30,300 lb | (2)-25 ft | 4 | 35 tons | 90124 | 1050C11-S | Consult |
| 60 ft | 100 tons | 36,000 lb | (2)-30 ft | 4 | 35 tons | 90128 | 1060C11-S | Consult |
| 70 ft | 100 tons | 42,100 lb | (1)-30 ft, (1)-40 ft | 5 | 30 tons | 90134 | (A) 1070C11-S | Consult |
| 70 ft | 100 tons | 43,100 lb | (2)-35 ft | 6 | 35 tons | 90118 | (B) 1070C11-S | Consult |
| 80 ft | 100 tons | 48,000 lb | (2)-40 ft | 6 | 35 tons | 90141 | 1080C11-S | Consult |
| SURVIVOR | ATV-M - Steel De | eck - 12 Foot Width | | | | | | |
| 30 ft | 50 tons | 18,800 lb | 1 | 2 | 35 tons | 90073 | 530C12-S | Consult |
| 35 ft | 75 tons | 22,600 lb | 1 | 3 | 35 tons | 90077 | 735C12-S | Consult |
| 40 ft | 75 tons | 25,300 lb | 1 | 3 | 35 tons | 90081 | 740C12-S | Consult |
| 50 ft | 100 tons | 32,200 lb | (2)-25 ft | 4 | 35 tons | 90110 | 1050C12-S | Consult |
| 60 ft | 100 tons | 38,200 lb | (2)-30 ft | 4 | 35 tons | 90111 | 1060C12-S | Consult |
| 70 ft | 100 tons | 44,700 lb | (1)-30 ft (1)-40 ft | 5 | 30 tons | 90119 | (A) 1070C12-S | Consult |
| 70 ft | 100 tons | 45,700 lb | (2)-35 ft | 6 | 35 tons | 90120 | (B) 1070C12-S | Consult |
| 80 ft | 100 tons | 51,000 lb | (2)-40 ft | 6 | 35 tons | 90143 | 1080C12-S | Consult |

*Lengths of SURVIVOR ATV-M scales are the O.D. measurement at the scale frame(s)

Part Number/Price

| Part # | Description | Price |
|-----------|---|---------|
| ITCM Kits | | |
| 17856 | ITCM Mount Assembly, 1,500 lb with load cell | Consult |
| 17857 | ITCM Mount Assembly, 2,000 lb with load cell | Consult |
| 17864 | ITCM Mount Assembly, 5,000 lb with load cell | Consult |
| Bulkheads | | |
| 90715 | Bulkheads, set of (2) 12 ft wide for 10 ft wide ATV-M | Consult |
| 90718 | Bulkheads, set of (2) 13 ft wide for 11 ft wide ATV-M | Consult |
| 90720 | Bulkheads, set of (2) 14 ft wide for 12 ft wide ATV-M | Consult |