

BenchMark™

Stainless Steel



Specifications

Load Cell, OIML Certified:
Aluminum, environmentally sealed

Output Impedance:
350 ohms

Overload Protection:
Five point, independently adjusted

Cable Length:
3 m

Compensated Temperature Range:
-10° C to 40° C

Warranty:
Two-year limited warranty

Standard Features

- 304 stainless steel construction
- LifeGuard™ base design isolates load cell from overloads and shock loads for added durability
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces

Approvals



Additional models are available with the approvals shown here
Please consult the factory for part numbers.



Measurement
Canada
Approved



Part Number/Price

Part #	Capacity	Dimensions	Est. Weight	Price
120869	3 kg	254 x 254 x 92 mm	7,7 kg	Consult
120870	6 kg	254 x 254 x 92 mm	7,7 kg	Consult
120872	15 kg	254 x 254 x 92 mm	7,7 kg	Consult
120874	15 kg	305 x 305 x 105 mm	9 kg	Consult
120875	30 kg	305 x 305 x 105 mm	9 kg	Consult
124354	30 kg	305 x 457 x 105 mm	16,8 kg	Consult
124357	30 kg	457 x 457 x 133 mm	31 kg	Consult
124365	30 kg	457 x 610 x 133 mm	35,4 kg	Consult
120876	60 kg	305 x 305 x 133 mm	9 kg	Consult
124356	60 kg	305 x 457 x 133 mm	16,8 kg	Consult
124358	60 kg	457 x 457 x 133 mm	31 kg	Consult
124366	60 kg	457 x 610 x 133 mm	35,4 kg	Consult
124373	60 kg	610 x 610 x 133 mm	38 kg	Consult
124362	150 kg	457 x 457 x 133 mm	31 kg	Consult
124370	150 kg	457 x 610 x 133 mm	35,4 kg	Consult
124377	150 kg	610 x 610 x 133 mm	38 kg	Consult
124363	300 kg	457 x 475 x 133 mm	31 kg	Consult
124371	300 kg	457 x 610 x 133 mm	35,4 kg	Consult
124378	300 kg	610 x 610 x 133 mm	38 kg	Consult

Options/Accessories

Part #	Description	Price
112044	305 mm column for CW-90, CW-90X, 480 and 482 Legend™ Series	Consult
112045*	457 mm column for CW-90, CW-90X, 480 and 482 Legend™ Series	Consult
64576	Attachment bracket for 480 and 482 Legend™ Series	Consult
22125	Additional operating manual	Consult
N/A	Installation, testing, configuration and verification	Consult factory

* Not recommended for use with scale bases smaller than 305 x 305 mm

Dimensions

Part #	Capacity	Platform Size L/W	L1	W1	H
120869	3 kg	254 x 254 mm	268 mm	268 mm	92 mm
120870	6 kg	254 x 254 mm	268 mm	268 mm	92 mm
120872	15 kg	254 x 254 mm	268 mm	268 mm	92 mm
120874	15 kg	305 x 305 mm	318 mm	318 mm	105 mm
120875	30 kg	305 x 305 mm	318 mm	318 mm	105 mm
124354	30 kg	305 x 457 mm	318 mm	476 mm	105 mm
124357	30 kg	457 x 457 mm	476 mm	476 mm	133 mm
124365	30 kg	457 x 610 mm	476 mm	476 mm	133 mm
120876	60 kg	305 x 305 mm	318 mm	318 mm	133 mm
124356	60 kg	305 x 457 mm	318 mm	476 mm	133 mm
124358	60 kg	457 x 457 mm	629 mm	476 mm	133 mm
124366	60 kg	457 x 610 mm	629 mm	476 mm	133 mm
124373	60 kg	610 x 610 mm	629 mm	476 mm	133 mm
124362	150 kg	457 x 457 mm	629 mm	476 mm	133 mm
124370	150 kg	457 x 610 mm	629 mm	476 mm	133 mm
124377	150 kg	610 x 610 mm	629 mm	476 mm	133 mm
124363	300 kg	457 x 475 mm	629 mm	476 mm	133 mm
124371	300 kg	457 x 610 mm	629 mm	476 mm	133 mm
124378	300 kg	610 x 610 mm	629 mm	629 mm	133 mm

