# Entris® II Series Basic Advanced

## **Standard Features**

- User-friendly operation
- · Basic applications
- Monolithic weighing systems
- Aluminum die-cast base, ABS housing
- · Front level bubble
- RS-232 standard
- Below balance weighing

# **Specifications**

## Weighing Units:

Gram, kilogram, ounce, pound, carat, pennyweight, troy ounce, grain, newton (see technical manual for complete listing)

## **Operating Modes:**

Weighing, density, percentage, counting, mass unit conversion, mixing, statistics, components, animal weighing, checkweighing, peak hold and pipette test

#### Power:

AC adapter, 115 to 240 V, US plug

#### Stabilization Time:

BCA223I-1S: 2.5 seconds BCA323I-1S: 1.1 seconds

BCA423I-1S, BCA623I-1S: 1.0 seconds

BCA1203I-1S: 1.5 seconds

## **Calibration Weight:**

BCA223I-1S, BCA323I-1S: 200 g BCA423I-1S, BCA623I-1S, BCA1203I-1S: 500 g

#### Temperature:

Operating:

41 °F to 104 °F (5 °C to 40 °C)

## **Humidity:**

15% to 80% for temperatures up to 31  $^{\circ}\text{C}$ 

#### Est. Weight:

BCA223I-1S, BCA323I-1S, BCA423I-1S: 13.7 lb (6.2 kg) BCA623I-1S: 13.9 lb (6.3 kg) BCA1203I-1S: 12 lb (5.4 kg)

# Warranty:

Two-year limited

#### Return Policy:

Sartorius standard policy - restock fee may apply

| Model       | Capacity | Readability | Repeatability | Linearity | Pan Size           | Dimensions                                       | Part # | List Price |
|-------------|----------|-------------|---------------|-----------|--------------------|--|--------|------------|
| BCA223I-1S  | 220 g    | 1 mg        | ±0.1 mg       | ±0.2 mg   | 4.7 in<br>(120 mm) | 20.67 × 19.49 × 15.75 in (525 × 495 × 400 mm)    | 202470 | Consult    |
| BCA323I-1S  | 320 g    | 1 mg        | ±1 mg         | ±2 mg     | 4.7 in<br>(120 mm) | 20.67 × 19.49 × 15.75 in<br>(525 × 495 × 400 mm) | 202472 | Consult    |
| BCA423I-1S  | 420 g    | 1 mg        | ±1 mg         | ±2 mg     | 4.7 in<br>(120 mm) | 20.67 × 19.49 × 15.75 in (525 × 495 × 400 mm)    | 202474 | Consult    |
| BCA623I-1S  | 620 g    | 1 mg        | ±1 mg         | ±2 mg     | 4.7 in<br>(120 mm) | 20.67 × 19.49 × 15.75 in<br>(525 × 495 × 400 mm) | 202475 | Consult    |
| BCA1203I-1S | 1,200 g  | 1 mg        | ±1 mg         | ±2 mg     | 4.7 in<br>(120 mm) | 20.67 × 19.49 × 15.75 in (525 × 495 × 400 mm)    | 202478 | Consult    |

# **Options/Accessories**

| , p. 10. 10. 10. 10. 10. 10. 10. 10. 10. 10 |            |   |         |  |  |  |  |
|---|------------|---|---------|--|--|--|--|
| Part#                                       | Model#     | Description   | Price   |  |  |  |  |
| 112261                                      | YDP20-OCE  | Data printer (printer requires power supply part number 191429)             | Consult |  |  |  |  |
| 31103                                       | 6906937    | Paper rolls, one roll   | Consult |  |  |  |  |
| 31106                                       | 6906918    | Ink ribbon cassette   | Consult |  |  |  |  |
| 201911                                      | YCC-D09MF  | Data Cable RS-232, DB-9M to DB-9F (For YDP20 Printer)                       | Consult |  |  |  |  |
| 204042                                      | YEPS01-PS8 | Replacement AC adapter with interchangeable plugs (included with Entris II) | Consult |  |  |  |  |
| 191429                                      | YEPS01-PS4 | AC adapter with interchangeable plugs (for use with YDP20-0CE printer)      | Consult |  |  |  |  |

