CW-90

Over/Under Checkweigher





Approvals

Standard Features

- Membrane keypad consisting of zero, units, print, tare, over, under, ID, target, 0-9, clear, decimal, enter, menu, power
- · 304 stainless steel, IP66 rated indicator
- PreVent[™] breather vent
- Storage for up to 50 IDs
- Unit of measure: kg, gm, lb, oz, lb/oz (lb/oz is not Legal for Trade)
- · High-intensity LED display
- · Battery backed time and date
- Two full duplex RS-232 serial ports
- · Configurable print formats
- · Audit trail tracking
- · Optional communications: Ethernet, USB or fiber optic
- Four configurable Digital I/O
- · Reflash memory to upgrade firmware

Scale:

- · Aluminum, environmentally sealed load cell
- 304 stainless steel
- Meets HACCP requirements
- · Five point overload protection

Additional models are available with the approvals shown here Please consult the factory for part numbers.







Specifications

Power - AC:

Line voltages: 230 VAC Frequency: 50/60 Hz

Power Consumption:

0,75A at 230VAC (8W)

Excitation Voltage:

+5 VDC 8 x 350 Ω or

 $16 \times 700 \Omega$ load cells

Analog Signal Input Range:

-0,5 mV/V - 4,5 mV/V

Analog Signal Sensitivity:

 $0.3\,uV/graduation$ minimum, $1.5\,uV/graduation$ recommended

Measurement Rate:

960, 480, 240, 120, 60, 30, 15, 7,5 per second

System Linearity:

± 0,01% full scale

Digital I/0:

Four channels on CPU board

Circuit Protection:

RFI, EMI, ESD protection

Display:

Large 20 mm 14 segment, six-digit high-intensity red LED display

Status Annunciators:

Designators for percent, kg, gm, lb, oz, center of zero, G/B, N, T, PT, neg, motion

Operating Temperature:

Legal: -10°C to 40°C

Rating/Material:

IP66, stainless steel

Display Resolution:

100.000 graduations maximum

Load Cell:

Aluminum, environmentally sealed

Warranty:

Two-year limited warranty

Part Number/Price

| Part # | Capacity | Platform Dimensions | Column Height | Est. Weight | Price |
|-----------|-------------------------|---------------------|---------------|----------------|---------|
| 230 VAC (| CE marked/OIML approved | | | | |
| 106123 | 3 x 0,001 kg | 254 x 254 x 108 mm | 305 mm | 13,2 kg | Consult |
| 106124 | 6 x 0,002 kg | 254 x 254 x 108 mm | 305 mm | 13,2 kg | Consult |
| 106125 | 15 x 0,005 kg | 254 x 254 x 108 mm | 305 mm | 13,2 kg | Consult |
| 106126 | 15 x 0,005 kg | 305 x 305 x 108 mm | 305 mm | 15 kg | Consult |
| 106127 | 30 x 0,01 kg | 305 x 305 x 108 mm | 305 mm | 15 kg | Consult |
| 106128 | 60 x 0,02 kg | 305 x 305 x 108 mm | 305 mm | 15 kg | Consult |



Options/Accessories

| Part # | Description | Price |
|----------|--|---------|
| 77142 | Ethernet TCP/IP | Consult |
| 108671 | Wireless LAN card Wi-Fi 802,11 A/B | |
| 93245 | USB Port (PC connection only) cable included | Consult |
| 95357 | USB cable, Type A to mini-B, 1 meter | Consult |
| 96736 | Fiber optic board | Consult |
| 78026 | Fiber optic, duplex cable 30,480 mm | Consult |
| 80892 | Fiber optic cutter | Consult |
| 117358 | WeighVault™ (requires part number 77142 or 108671) | Consult |
| Consult* | Calibration without certificate | |
| Consult* | Verification 0-30 kg with certificate | Consult |
| Consult* | Verification 30-150 kg with certificate | Consult |

^{*}Verification service fees are net charges, no discount



