

Healthweigh®

350-ADA-1

DUAL-RAMP ADA-COMPLIANT WHEELCHAIR SCALE

www.ricelake.com/ada-compliant



RICE LAKE®
WEIGHING SYSTEMS

800-472-6703

www.ricelake.com

Safe, Compliant Healthcare with Rice Lake

The Healthweigh 350-ADA-1 is a safe and inclusive patient weighing solution from Rice Lake Weighing Systems. It is a foldable wheelchair scale designed to serve bariatric patients and those with varying mobility levels by meeting the Americans with Disabilities Act (ADA) standards for public healthcare facilities and assisted living homes.



The ADA regulates medical equipment to ensure resources are devoted to accessibility for those who need extra assistance, such as bariatric patients or individuals using wheelchairs. This includes regulations for medical scales. In 2024, the U.S. Access Board introduced updates that specifically address medical diagnostic equipment (MDE), setting clear guidelines for accessibility.

As of August 9, 2026, every public healthcare facility must have at least one ADA-compliant scale, or 10% of all diagnostic

equipment must meet ADA requirements. For a scale to be ADA-compliant, it must have a certain platform width, depth, slope and edge protection on the ramps and platform.

The 350-ADA-1 is built to meet ADA standards and provide the best patient experience. Its compact and foldable design makes it easy to store and keeps spaces open for patient comfort. With integrated wheels, it can be moved to different rooms to weigh patients where it's most convenient for them. For a comfortable, safe weighing experience, the 350-ADA-1 features:

35-INCH HANDRAIL

Sturdy handrail along the scale platform so patients can comfortably stand or move

1

40-INCH WEIGHING PLATFORM

Large platform to provide accessibility to wheelchairs and bariatric patients

2

2-INCH EDGE PROTECTION

Edge protection to avoid slipping off the scale

3

1:8 RAMP SLOPE

Slow incline to easily move across the scale

4



Easy to store, folded depth is 11.75 in (29.8 cm)



Fire exit

Pathology



*Integrated wheels
make transportation
of the scale easy*



1:8 Slope

350-ADA-1

DUAL-RAMP ADA-COMPLIANT WHEELCHAIR SCALE

Healthweigh®



Rice Lake Weighing Systems has been manufacturing and distributing weight-related products since 1946. Today, Rice Lake Weighing Systems is a global leader in the weighing industry, providing innovative weighing, measuring and process control systems.

Learn more about how the Healthweigh 350-ADA-1 wheelchair scale makes patient weighing easier and meets ADA standards.

www.ricelake.com/ada-compliant

PART NUMBER	DESCRIPTION	CAPACITY
231628	350-ADA-1	1,000 x 0.2 lb (450 x 0.1 kg) with USB

Verified Through Third-party Corada Assessment

Rice Lake's 350-ADA-1 is a Corada Platinum certified product. Corada certified scales meet applicable ADA Standards when installed, maintained and operated correctly. It's the only certification that reliably ensures ADA compliance, proving the 350-ADA-1 delivers inclusive patient care.



STANDARD FEATURES

- ADA-Compliant
- Large LCD display
- Antimicrobial keypad
- Dual ramp
- Metal, nonslip platform
- Supports bariatric patient weighing
- 2-inch edge protection
- 1:8 gentle slope
- Two wheels for easy transport
- Motiontrap™ movement compensation technology
- Unit of measure toggle or locking
- EMR capable
- Serial and USB data communication ports
- Tare function
- Hold function
- Body mass index (BMI) function
- Factory calibrated
- Easy to store, folded depth is 11.75 in (29.8 cm)

OPTIONS

- 9 VDC adapter, 120 V/230 V auto switching
- 9 VDC adapter, 230 V
- Epson TM-U220 Tape Printer
- Printer cable, 25-pin D-Sub male to RJ-45, 6 ft

SPECIFICATIONS

CAPACITY:	1,000 x 0.2 lb (450 x 0.1 kg)
PLATFORM DIMENSIONS:	(L) 40.60 in x (W) 32.00 in x (H) 4.50 in
POWER:	9 VDC, provided by six AA alkaline batteries (included) or AC adapter (optional)
BATTERY TYPE:	Six AA alkaline (included)
BATTERY USE:	25 hours of continuous use with batteries Automatic power-off can be configured
DISPLAY:	5-digit LCD display, 0.75 in (1.9 cm) digit height
TEMPERATURE:	Operating: 50 °F to 104 °F (10 °C to 40 °C)

WARRANTY

- Two-year limited