

# RS-130 and RS-160

BATTERY-OPERATED PRICE COMPUTING SCALES



**RICE LAKE**<sup>®</sup>  
WEIGHING SYSTEMS

800-472-6703

[www.ricelake.com](http://www.ricelake.com)

# RS-130 and RS-160

BATTERY-OPERATED PRICE COMPUTING SCALES

## Accurate, Affordable and Portable

The RS-130 and RS-160 retail scales are the ultimate choice for simple price computing applications. Delivering unmatched convenience and accuracy, the RS-130 and RS-160 provide one-button operation with weight displays in either pounds, kilograms or ounces.

For added convenience, the RS-130 and RS-160 can toggle units of measure and save tare, price and nine direct price lookups. Cash back calculation allows you to quickly provide cash back for applications where a cash register is not present. The scales' large, stainless steel platters provide ample room for product, and standard in-use covers assure years of trouble-free operation.

The RS-130 and RS-160 are NTEP Certified and powered by an included rechargeable battery. A low-battery annunciator signals the operator when it's time to recharge. The RS-130 and RS-160 offer the most accurate, portable and affordable solutions for simple price computing needs.



RS-130 bench model pictured with backlight on



RS-160 pole model



Easy-to-read displays on the back of the RS-130 and RS-160 allow viewing by the customer.

## STANDARD FEATURES

- Toggle between pounds/kilograms/ounces
- Nine PLU keys for direct price lookups
- Cash back calculation
- Large, stainless steel platter
- Easy-to-read backlit displays
- In-use cover
- Battery charge indicator
- Included internal, sealed battery
- NTEP-Certified Legal for Trade

## SPECIFICATIONS

<b>RS-130 CAPACITY/GRADUATIONS:</b>	30 x 0.01 lb/15 x 0.005 kg/480 x 0.2 oz
<b>RS-160 CAPACITY/GRADUATIONS:</b>	60 x 0.02 lb/30 x 0.01 kg/960 x 0.5 oz
<b>ACCURACY:</b>	1/3000
<b>DISPLAY ITEMS:</b>	Weight: Five digits Unit price: Five digits Total price: Six digits
<b>DISPLAY TYPE:</b>	Backlit LCD displays with 0.453-in (11.5-mm) character height
<b>ZERO TRACKING:</b>	Automatic; center zero accuracy of $\pm 1/2$ division; maximum range of $\pm 2\%$
<b>POWER SOURCE:</b>	DC 6 V/25 mA rechargeable battery with AC adapter included, AC 115 V/0.1 A (max)
<b>DIMENSIONS:</b>	Platter (W x D): 11.8 x 9.5 in Bench model overall (W x D x H): 12.3 x 13.0 x 4.7 in Pole model overall (W x D x H): 12.3 x 13.0 x 4.7 in
<b>WEIGHT:</b>	10 lb (4.5 kg)
<b>TEMPERATURE RANGE:</b>	Storage: 5° to 140° F (-15° to 60° C) Operating: 32° to 104° F (0° to 40° C)
<b>WARRANTY:</b>	One-year limited warranty

## APPROVALS:

