
Vehicle Scales

TABLE OF CONTENTS

Vehicle Scales	929
SURVIVOR® Truck and Rail Scales	930
RailBoss®	931
RoughDeck® AX	934
AX3040	935
RoughDeck® AX-1	936
Load Ranger <i>Wireless Wheel Pad Scale</i>	938
Load Ranger Cart	940

SURVIVOR® Truck and Rail Scales

For more information on Rice Lake's full line of SURVIVOR® truck and rail scales, please visit our website at www.ricelake.com or call 800-472-6703 and ask to speak with a heavy capacity team member.



Truck Scales:

www.ricelake.com/survivor

SURVIVOR OTR

Heavy-duty, top access, concrete or steel deck scales

SURVIVOR OTR-LP

Heavy-duty, steel deck, low-profile scale for existing foundations

SURVIVOR OTR-XV

Extreme-duty, top access, concrete or steel deck scales

SURVIVOR ATV

Heavy- or extreme-duty, top access portable steel deck scales

SURVIVOR SR

Heavy-duty, low-profile, concrete or steel deck siderail scales

SURVIVOR PT

Heavy-duty, pit-type, concrete or steel deck scales

SURVIVOR Multi-Platform

Weigh In-motion OTR concrete or steel deck scales

SURVIVOR ATV-M

Portable, self-contained levertronic, steel deck scales

SURVIVOR PT-M

Pit-type, levertronic, concrete deck scales

Rail Scales:

www.ricelake.com/railscales

SURVIVOR RT

Pit-type, rail/truck combination scales


SURVIVOR PL

Low-profile, pitless scales

RailBoss®

Full- or double-draft rail scales

RailBoss®





Approvals





Part Number/Price

Part #	Description	Est. Weight	Price
Kits			
164748	RailBoss assembly kit, full draft, 90 RA rail V2	2,280 lb	\$40,900.00
164749	RailBoss assembly kit, double draft, 90 RA rail V2	1,150 lb	\$20,400.00
193391	RailBoss assembly kit, full draft, 100 ARAA	2,500 lb	\$41,100.00
193390	RailBoss assembly kit, double draft, 100 ARAA	1,100 lb	\$20,500.00
215172	RailBoss assembly kit, full draft, 100 ARAA	2,300 lb	\$46,000.00
188023	RailBoss assembly kit, double draft, 100 AREA	1,100 lb	\$21,500.00
162515	RailBoss assembly kit, full draft, 115 RE rail V2	2,550 lb	\$41,100.00
162516	RailBoss assembly kit, double draft, 115 RE rail V2	1,275 lb	\$20,500.00
164752	RailBoss assembly kit, full draft, 132 RE rail V2	2,800 lb	\$41,500.00
164753	RailBoss assembly kit, double draft, 13 2RE rail V2	1,400 lb	\$20,800.00
194678	RailBoss assembly kit, full draft, 133 AREA	2,900 lb	\$41,500.00
194679	RailBoss assembly kit, double draft, 133 AREA	1,450 lb	\$20,800.00
169763	RailBoss assembly kit, full draft, 136 AREA	3,000 lb	\$43,600.00
169762	RailBoss assembly kit, double draft, 136 AREA	1,500 lb	\$21,900.00
Single Rail	Gauge Assemblies		
164750	RailBoss 90 lb gauge assembly V2 (does not include cable)	290 lb	\$5,400.00
193389	RailBoss 100 ARAA gauge assembly V2 (does not include cable)	300 lb	\$5,400.00
188013	RailBoss 100 ARAA gauge assembly V2 (does not include cable)	320 lb	\$5,400.00
162517	RailBoss 115 lb gauge assembly V2 (does not include cable)	320 lb	\$5,400.00
164754	RailBoss 132 lb gauge assembly V2 (does not include cable)	350 lb	\$5,400.00
194677	RailBoss 133 AREA gauge assembly V2 (does not include cable)	370 lb	\$5,400.00
169761	RailBoss 136 AREA gauge assembly V2 (does not include cable)	390 lb	\$5,400.00

NOTE: Instrumentation with RailBoss software must be ordered separately and is not included with the RailBoss assembly kit

Standard Features

- · Full-draft or double-draft
- 80,000 lb axle capacity
- 320,000 lb full scale capacity
- 40,000 lb rail section capacity
- 90 RA, 100 ARA-A, 115 RE, 132 RE, 133 RE or 136 RE rail sections
- 5 ft 10 in rail sections, pre-drilled for joint bars
- Quick-disconnect cable connection with MS style connector

Full-draft Package Includes

- Eight 5 ft 10 in rail sections
- 30 ft of connecting cable per rail section
- Pre-drilled joint bars with connection hardware
- Two Rice Lake junction boxes with transient protection
- 30 ft of homerun cable

Double-draft Package Includes

- Four 5 ft 10 in rail sections
- 30 ft of connecting cable per rail section
- Pre-drilled joint bars with connection hardware
- One Rice Lake junction box with transient protection
- 30 ft of homerun cable

Optional Features

- Custom rail sizes are available
- 1280 Enterprise™ Series indicator with RailBoss software for full-draft or double-draft applications*
- 920i® indicator with RailBoss software for full-draft or double-draft applications*
- Custom cable lengths *Non-Legal for Trade

Calibration Unit Standard Features

- 482 Legend® Series indicator
- Attachment hardware for 90 RA, 115RE and 132RE rail

Specifications

Load Cells:

40,000 lb

Accuracy:

± 0.25% error typical, interchangeable with other gauged rail products

Full Scale Output:

0.8 mV/V ± 0.2%

Input Resistance:

 $765 \pm 5 \text{ ohm}$

Output Resistance:

 $700 \pm 5 \text{ ohm}$

Full Scale Capacity:

320,000 lb

Axle Capacity:

80,000 lb Warranty:

Two-year limited Intrinsic Safety:

Class I, II, III, Division 1, Groups ABCDEFG





Part Number/Price


Part #	Description	Est. Weight	Price
Instrumentation	n		
190949	Single-channel 1280 indicator double draft with RailBoss software	11 lb	\$3,850.00
190951	Dual-channel 1280 indicator full draft with RailBoss software	11 lb	\$4,050.00
190952	Three-channel 1280 indicator full draft with RailBoss software	11 lb	\$4,525.00
Hardware			
126391	90 RA 24 in short toe joint bar set, 4 sets required (2 bars with bolts and nuts)	40 lb	\$1,350.00
129620	100 RE short toe joint bar set, 4 sets required (2 bars with bolts and nuts)	58 lb	\$1,225.00
193468	100 ARAA short tow joint bar set, 4 sets required (2 bars with bolts and nuts)	45 lb	\$1,225.00
126389	115 RE 24 in short toe joint bar set, 4 sets required (2 bars with bolts and nuts)	50 lb	\$1,050.00
126390	132 RE 24 in short toe joint bar set, 4 sets required (2 bars with bolts and nuts)	60 lb	\$1,225.00
194674	133 AREA short tow joint bar set, 4 sets required (2 bars with bolts and nuts)	70 lb	\$1,225.00
126390	136 AREA short tow joint bar set, 4 sets required (2 bars with bolts and nuts)	80 lb	\$1,225.00
126111	90 RA isolation joint bar set, 4 sets required (2 bars with bolts and nuts)	40 lb	\$1,225.00
112702	115 RE isolation joint bar set, 4 sets required (2 bars with bolts and nuts)	50 lb	\$1,225.00
119771	132 RE isolation joint bar set, 4 sets required (2 bars with bolts and nuts)	60 lb	\$1,225.00
194673	133 AREA isolation joint bar set, 4 sets required (2 bars with bolts and nuts)	70 lb	\$1,225.00
194344	136 AREA isolation joint bar set, 4 sets required (2 bars with bolts and nuts)	80 lb	\$1,225.00
198086	100 RA isolation joint bar set, 4 sets required (2 bars with bolts and nuts)	-	\$1,225.00
163004	30 ft interface cable	-	\$625.00
164873	60 ft interface cable	-	\$775.00
164874	100 ft interface cable	-	\$1,050.00
188909	Adapter cable from AWT Weighline to Rice Lake RailBoss	-	\$650.00
Calibration Eq	uipment		
115564	RailBoss calibration/test unit	300 lb	\$12,900.00
119068	RailBoss calibration/test until rental (one week)	300 lb	\$800.00
208171	Coupler, flush face, no drip for Enerpac FR400 pump	-	\$425.00


NOTE: Instrumentation with RailBoss software must be ordered separately and is not included with the RailBoss assembly kit.











Full-draft RailBoss software display with a 1280 indicator




Double-draft RailBoss software display with a 920i indicator



Part Number/Price

Part #	Description	Dimensions (L × W × H)	Est. Weight	Price
107637	60,000 lb (30,000 lb each)	84 × 32 × 6 in	3,600 lb	\$17,495.00



Standard Features

System includes two platforms with anchor brackets and four on/off ramps with anchor tabs (anchor bolts not included)

Scale

- (L × W × H) 84 × 32 × 6 in
- Axle capacity, tandem platforms: 60,000 lb (two scales 30,000 lb each)
- Includes two 3/4-10 NC eye bolts for lifting scale during installation
- Contains four environmentally sealed, IP67 20,000 lb single-ended shear beam load cells per platform
- · Treaded top plate with side access junction box
- JB4SS TuffSeal® signal trim junction box
- · Top access foot adjustment holes
- Carbon steel captured ball feet
- 20 ft SURVIVOR® EL147HE cable
- Non-Legal for Trade

Ramps

- (L × W × H) 60 × 32 × 6 in
- Treaded top plate

Specifications

End Loading Capacity: 133% full scale at 30,000 lb

Warranty:

Load cells: Two-years

All other components: One-year limited

Dimensions

Roug	JhDeck AX
Α	84.00 in
В	32.00 in
С	205.50 in
D	38.75 in
Е	6.00 in
F	1.00 in
G	0.75 in


Note: 1 in = 25.4 mm





Part Number/Price

Part #	Description	Dimensions (L × W × H)	Est. Weight	Price
Steel Consti	ruction - Painted Black 2 Scales	with Connecting Cables a	nd 4 Ramps	
112330	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	2,500 lb	\$15,595.00
111748	80,000 lb (40,000 lb each)	12 ft × 2.5 ft × 5.63 in	4,400 lb	\$18,450.00
112328	80,000 lb (40,000 lb each)	14 ft × 2.5 ft × 5.75 in	5,200 lb	\$24,495.00
Steel Consti	ruction - Painted Black 2 Scales	with Connecting Cables, \	Without Ramps	
204097	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	2,500 lb	\$13,095.00
204099	80,000 lb (40,000 lb each)	12 ft × 2.5 ft × 5.63 in	4,400 lb	\$15,950.00
204100	80,000 lb (40,000 lb each)	14 ft × 2.5 ft × 5.75 in	5,200 lb	\$21,995.00
Aluminum C	Construction - Glass Beaded 2 Sc	ales with Connecting Cab	les and 4 Ramps	
112329	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	1,250 lb	\$18,375.00
Aluminum C	Construction - Glass Beaded with	Connecting Cables, With	out Ramps	
204101	60,000 lb (30,000 lb each)	7 ft × 2.5 ft × 5.63 in	1,250 lb	\$15,395.00
Ramps with	Hardware (Qty. 2)			
204102	(2) Ramps steel construction - painted black with hardware			\$1,265.00
204103	(2) Ramps aluminum construc	tion - glass beaded with ho	ardware	\$1,495.00





Standard Features

Scales

- Sizes: 7 ft, 12 ft and 14 ft lengths
- Steel or aluminum construction
- Axle capacity, tandem platforms: 60,000 or 80,000 lb (30,000 or 40,000 lb each)
- Includes four 5/8-11 NC eye bolts for lifting scale during installation
- Contains two load cells per platform
- Treaded top plate with four lifting eyes
- JB4SS TuffSeal® signal trim junction box
- 10 ft EL146HE Interconnect cable with MS-type connectors to go between weigh pads
- 50 ft EL147HE cable to connect weigh pad to indicator
- · Non-Legal for Trade

Ramps

- (L \times W) 7 ft and 12 ft scales: 5.63 \times 32.00 in, 14 ft scale: 5.75 \times 32.00 in
- Steel or aluminum
- · Anchor bolts not included

Specifications

Construction:

Steel or aluminum

Accuracy:

±3%

End Loading Capacity:

133% full scale at 30,000 lb 100% full scale at 40,000 lb

Warranty:

One-year limited

Dimensions

A	AX3040			
7 f	t steel			
Α	83.60 in	Е	31.00 in	
В	90.90 in	F	32.00 in	
С	141.25 in	G	5.63 in	
D	30.00 in			
12	ft steel			
Α	143.60 in	E	31.00 in	
В	150.90 in	F	32.00 in	
С	201.2 in	G	5.63 in	
D	30.00 in			
14	ft steel			
Α	167.60 in	E	31.00 in	
В	174.90 in	F	32.00 in	
С	225.25 in	G	5.75 in	
D	30.00 in			
7 f	t aluminum			
Α	83.60 in	E	31.00 in	
В	90.90 in	F	32.00 in	
С	141.25 in	G	5.63 in	
D	30.00 in			

Note: 1 in = 25.4 mm

RoughDeck® AX-1



Part Number/Price

Part #	Dimensions (L ×W × H)	Capacity	Est. Weight	Price
Scale only				
169649	7.5 ft × 9.6 ft × 6.0 in	50,000 lb	3,350 lb	\$17,375.00
169650	9.5 ft × 9.6 ft × 6.0 in	50,000 lb	4,150 lb	\$19,575.00
169651	11.5 ft × 9.6 ft × 6.0 in	50,000 lb	5,500 lb	\$21,735.00
Scale, bundle	d with scale frame			
169645	8.0 ft × 10.1 ft × 6.75 in	50,000 lb	4,350 lb	\$19,995.00
169647	10.0 ft × 10.1 ft × 6.75 in	50,000 lb	5,400 lb	\$22,675.00
169648	12.0 ft × 10.1 ft × 6.75 in	50,000 lb	7,000 lb	\$26,895.00

Options/Accessories

10000001100			
Dimensions (L × W × H)	Est. Weight	Price	
nly			
8.0 ft × 10.1 ft × 6.75 in	1,000 lb	\$3,040.00	
10.0 ft × 10.1 ft × 6.75 in	1,250 lb	\$3,535.00	
12.0 ft × 10.1 ft × 6.75 in	1,500 lb	\$5,395.00	
es to scale frame			
10 × 4 ft, single ramp	1,600 lb	\$3,545.00	
10 × 4 ft, ramp set	3,200 lb	\$7,095.00	
Ramp, attaches to scale			
10 × 4 ft, single ramp	1,675 lb	\$3,545.00	
10 × 4 ft, ramp set	3,350 lb	\$7,095.00	
	Dimensions (L × W × H) nly 8.0 ft × 10.1 ft × 6.75 in 10.0 ft × 10.1 ft × 6.75 in 12.0 ft × 10.1 ft × 6.75 in 25 to scale frame 10 × 4 ft, single ramp 10 × 4 ft, ramp set 25 to scale 10 × 4 ft, single ramp	Dimensions (L × W × H) Est. Weight	

*Consult factory for quote on riser plate for opposite end of scale.



Standard Features

- Sizes: 7.5 ft, 9.5 ft or 11.5 ft lengths
- Capacity: 50,000 lb
- Includes two 1-8 NC eye bolts
- Contains four environmentally sealed, IP67, 20,000 lb single-ended load cells
- Treaded top plate
- JB4SS TuffSeal® signal trim top access junction box
- Top access foot adjustment holes
- Carbon steel captured ball feet
- 20 ft SURVIVOR® EL147HE cable
- Non-Legal for Trade

Options:

- Ramps: 10×4 ft, treaded top plate
- Scale frame

Specifications

End Loading Capacity: 80% full scale at 50,000 lb


Warranty:

Load cells: Two-years

All other components: One-year limited

RoughDeck® AX-1






Dimensions

Rou	RoughDeck AX-1			
PN 1	69649			
Α	90.00 in			
PN 1	PN 169650			
Α	114.00 in			
PN 169651				
Α	138 00 in			

Note: 1 in = 25.4 mm




Note: 1 in = 25.4 mm



Scale in scale frame with ramps

PN 169645			
Α	90.00 in	В	191.75 in
PN 169647			
Α	114.00 in	В	215.75 in
PN 169648			
Α	138.00 in	В	239.75 in

Note: 1 in = 25.4 mm



Scale with ramps

PN 169649				
A1	90.00 in	B1	187.00 in	
PN 169650				
A1	114.00 in	B1	211.00 in	
PN 169651				
A1	138.00 in	B1	235.00 in	

Note: 1 in = 25.4 mm

Load Ranger



Part Number/Price

Part #	Description	Est. Weight	Price
227314	Remote indicator with integrated printer in carrying case	15 lb	\$2,200.00

Part #	Size (W × L × H), Capacity	Est. Weight	Price		
RF-MD 2.4	RF-MD 2.4 GHz				
212096	1 ft 10 in × 1 ft 8 in × 2.28 in, 3,300 × 1 lb	40 lb	\$2,295.00		
212097	1 ft 10 in × 1 ft 8 in × 2.28 in, 6,600 × 2 lb	40 lb	\$2,295.00		
212098	1 ft 10 in × 1 ft 8 in × 2.28 in, 13,200 × 5 lb	40 lb	\$2,295.00		
212099	1 ft 10 in × 1 ft 8 in × 2.28 in, 22,000 × 10 lb	40 lb	\$2,495.00		
212100	1 ft 10 in × 1 ft 8 in × 2.28 in, 33,000 × 10 lb	40 lb	\$2,495.00		
RF-WD 2.4	GHz				
212101	2 ft 6 in × 1 ft 10 in × 2.28 in, 13,200 × 5 lb	65 lb	\$2,875.00		
212102	2 ft 6 in × 1 ft 10 in × 2.28 in, 22,000 × 10 lb	65 lb	\$2,875.00		
212103	2 ft 6 in × 1 ft 10 in × 2.28 in, 33,000 × 10 lb	65 lb	\$2,875.00		
RF-WD 2.4	GHz NTEP				
212835	2 ft 6 in \times 1 ft 10 in \times 2.28 in, 22,000 \times 20 lb (NTEP Class IIII)	65 lb	\$3,520.00		
RF-XWD 2.4 GHz					
212104	3 ft 1 in × 2 ft × 2.28 in, 13,200 × 5 lb	105 lb	\$3,520.00		
212105	3 ft 1 in × 2 ft × 2.28 in, 22,000 × 10 lb	105 lb	\$3,520.00		
212106	3 ft 1 in × 2 ft × 2.28 in, 33,000 × 10 lb	105 lb	\$3,520.00		
212107	3 ft 1 in × 2 ft × 2.28 in, 44,000 × 20 lb	105 lb	\$3,520.00		

Options/Accessories

Part #	Description	Price
181881	Aluminum ramp for Load Ranger MD models (single ramp only)	\$280.00
181882	Aluminum ramp for Load Ranger WD models (single ramp only)	\$310.00
181883	Aluminum ramp for Load Ranger XWD models (single ramp only)	\$340.00
182053	Printer paper roll, 57 mm x 30 m, 12 mm core 51 mm OD	\$3.00
185064	Load Ranger wheel pad charger, 110 VAC version with US plug	\$130.00
192591	Load Ranger Ai-1 remote indicator power adapter, 120-230 VAC version with US plug	\$95.00

Note: Bluetooth models are discontinued,

2.4 GHz models are not compatible with discontinued Bluetooth models without upgrade kits.

Standard Features

- Up to 16 individual pads communicate wireless to the indicator
- Industrial RF radio module to communicate with optional indicator
- Integrated wheels and nonslip rubber under platform
- internal rechargeable battery with 40 hours of battery life
- Built-in indicator on each scale with 1 in character display
- IP67 rating
- · Cover plate protects built-in indicator

Optional Remote Indicator with Integrated Printer in Carrying Case

- ABS carrying case: $1 \text{ ft} \times 1 \text{ ft } 6 \text{ in} \times 7 \text{ in}$
- Backlit graphic display with touchscreen technology
- · Internal battery with 10 hours of battery life
- · Real-time clock
- Permanent data storage
- · Direct thermal receipt printer

Wheel Weighing Software

- Multi-scale function mode weighs with up to 16 individual pads (eight sets)
- Static axle weighing function, up to two channels
- · Calculation of center of gravity
- Semi-automatic and preset tare
- · Selection of displayed data on LCD touchscreen
- 1,000 field database
- Print and display list of last 3,500 vehicles

Options/Accessories

- · Leveling modules
- · Aluminum ramps
- NTEP Class IIII (Select sizes and capacities only, consult factory for more information)

Specifications

Battery: NIMH, 6VDC, 4.5Ah, rechargeable. approx 40 hours

Charger: 120 VDC, UL approved wall adapter

Display:

1 in character display on each scale

System Accuracy:

0.05% of rated capacity

Communication: Wireless 2.4 GHz

Construction:

Aluminum alloy

Temperature:

Operating:

14 °F to 104 °F (-10 °C to 40 °C)

Storage:

-4 °F to 140 °F (-20 °C to 60 °C)

Effective Wireless Communication Range:

Up to 160 ft (50 m) line of sight typical

Warranty:

Two-year limited

Approvals:

NTEP 20-003P Class IIII




NTEP Class IIII approved for law enforcement.



Dimensions

Plat	Platform			
	RF-MD	RF-WD	RF-XWD	
Α	1 ft 8 in (511 mm)	1 ft 10in (564 mm)	2 ft (611 mm)	
В	2 ft (611 mm)	2 ft 8 in (813 mm)	3 ft 3 in (991 mm)	
С	2.28 in (58 mm)	2.28 in (58 mm)	2.28 in (58 mm)	
D	1 ft 4 in (406 mm)	1 ft 6 in (457 mm)	1 ft 8 in (511 mm)	
Е	1 ft 10in (564 mm)	2 ft 6 in (750 mm)	3 ft 1 in (950 mm)	

Loading Surface			
	RF-MD	RF-WD	RF-XWD
F	1 ft 3 in (381 mm)	1 ft 11 in (584 mm)	2 ft 5 in (737 mm)
G	1 ft 4 in (406 mm)	1 ft 6 in (457 mm)	1 ft 8 in (511 mm)





Optional aluminum ramps

Load Ranger Cart Transport Cart



Standard Features

- Can hold up to four, six or eight Load Ranger wheel pads (with or without optional ramps) and one Load Ranger remote indicator case
- Two swivel, locking casters and two rigid casters to insure the safety of the scales during transit
- Painted mild steel
- Bottom surface, heavy duty plastic to offer scratch resistance for Load Rangers
- Integrated forklift channels
- Cam latch closures
- AC power strip, US plug

Specifications

Warranty:

One-year limited

Part Number/Price

Part #	Description	Est. Weight	Price
225058	Load Ranger transport cart for up to 4 Load Ranger wheel pads	480 lb	\$3,995.00
203078	Load Ranger transport cart for up to 6 Load Ranger wheel pads	540 lb	\$4,595.00
221488	Load Ranger transport cart for up to 8 Load Ranger wheel pads	610 lb	\$5,595.00

Dimensions

Load Ranger Cart, 4 Bay					
Α	31.80 in (808 mm)	E	37.17 in (944 mm)		
В	24.75 in (629 mm)	F	7.80 in (198 mm)		
С	47.87 in (1,216 mm)	G	9.26 in (235 mm)		
D	43.50 in (1,105 mm)				
Load	Load Ranger Cart, 6 Bay				
Α	40.80 in (1,036 mm)	E	37.17 in (944 mm)		
В	24.75 in (629 mm)	F	7.80 in (198 mm)		
С	47.87 in (1,216 mm)	G	16.25 in (413 mm)		
D	43.50 in (1,105 mm)				
Load Ranger Cart, 8 Bay					
Α	50.30 in (1,278 mm)	E	37.17 in (944 mm)		
В	24.75 in (629 mm)	F	7.80 in (198 mm)		
С	47.87 in (1,216 mm)	G	25.75 in (654 mm)		
D	43.50 in (1.105 mm)				

