



Standard Features

- Simple operation, easy to set up
- Large six-digit backlight LCD display with 1-inch (29 mm) characters protected by heavy-duty tempered glass
- Powered USB HID point of sale interface, kg model only
- Nine-pin RS-232 interface for use with SMA and NCI protocols
- Four AA alkaline battery operation for portability
- Gravitational compensation allows for adjustment of factory calibration to meet your local gravity setting, non-approved

Specifications

- Power:**
In-line power supply (included)
- Input:**
100 to 240 VAC, +10% -15%, 3-wire w/ground
Terminated with standard USA 3-prong plug
- Output:**
12 V at 0.1 Amps DC minimum
- Frequency:**
50/60 Hz ± 3 Hz
- Power supply approvals:**
UL, CE, EN, CUL
- Battery Type:**
Four AA alkaline batteries, 6 V,
with low battery indication at 4.3 volts
- Battery Life:**
50 to 250 hrs depending on backlight and auto-shutdown settings
- Excitation:**
3.0 mV/V
- Resolution:**
Internal: 500,000 counts
- USB HID:**
USB 2.0 full speed; Vendor ID: 1C19;
Product ID: 0002

Approvals



Part Number/Price

Part #	Platform Capacity	Dimensions	Est. Weight	Price
187832	35 kg triple range	12 × 14 in	18 lb	Consult
195741	35 kg triple interval	12 × 14 in	18 lb	Consult
192361	70 lb dual range	12 × 14 in	18 lb	Consult
195742	70 lb dual interval	12 × 14 in	18 lb	Consult



Options/Accessories

Part #	Description	Est. Weight	Price
174783	Column bracket and post (12 × 14 scale only)	2 lb	Consult
180901	Second customer display, BenchPro BP-P no keyboard with 68 in cable	4 lb	Consult
174784	Second remote operator display, BenchPro BP-P with 68 in cable	4 lb	Consult
183103	16 in (H) tabletop display post for use with second display, customer or remote operator	4 lb	Consult
178501	USB RS-232 serial adapter 3.28 ft cable	1 lb	Consult

Dimensions

BenchPro BP-P			
A	12.00 in	C	14.50 in
B	14.00 in	D	2.70 in

Note: 1 in = 25.4 mm



BP-P shown with 183103 and 180901



Shown with 174783

Divisions (multi-range):

- kg triple range:**
0 to 5 kg × 0.001 kg
0 to 10 kg × 0.002 kg
0 to 35 kg × 0.01 kg
- lb/oz dual range:**
0 to 7 lb × 0.05 oz
0 to 70 lb × 0.2 oz

Divisions (Multi-Interval):

- kg triple interval:**
0 to 5 kg × 0.001 kg
5 to 10 kg × 0.002 kg
10 to 35 kg × 0.01 kg
- Lb/oz dual interval:**
0 to 7 lb × 0.05 oz
7 to 70 lb × 0.2 oz

Material:

Display: ABS plastic housing
Scale base: Die-cast aluminum load bridge and base housing with stainless steel weight platter

Dynamic Response:

Response time for stable weight:
0 to 1,000 d, 1,000 ms, maximum mean average
1,000 d +, 1,500 ms, maximum mean average

Overload Protection:

Corner and center overload protection

Display:

Large six-digit backlight LCD display with 1-inch (29 mm) Characters protected by heavy-duty tempered glass

Annunciators:

Six: zero, gross/brutto, net, W1/W2/W3 multi-range

Keys/Buttons:

Three: units, on/off, F1
(Tare is not applicable)
Minimum key press life of 500,000 cycles

RS-232 Cable (Included):

10 ft DB 9-pin male to female, straight pass-through

USB Cable (Included):

46 in (1,168 mm) A/B type USB cable

Warranty:

Two-year limited

Approvals:

NTEP 17-002
Canada Weights and Measures: AM - 6050
CE Marked