and shock loading · Spring steel flexures

cell and plated wire rope

smooth deck



Approvals

Part Number/Price

ruit Number/Frice								
Part#	Size (W × L × H)	Capacity	Est. Weight	Price				
Painted Steel								
33134	18 × 24 × 6.5 in	500 lb (250 kg)	125 lb	Consult				
33066	18 × 24 × 6.5 in	1,000 lb (500 kg)	125 lb	Consult				
113566	18 × 30 × 6.5 in	500 lb (250 kg)	133 lb	Consult				
33136	18 × 30 × 6.5 in	1,000 lb (500 kg)	133 lb	Consult				
113567	18 × 30 × 6.5 in	1,500 lb (750 kg)	133 lb	Consult				
33067	24 × 24 × 6.5 in	500 lb (250 kg)	151 lb	Consult				
33068	24 × 24 × 6.5 in	1,000 lb (500 kg)	151 lb	Consult				
33138	30 × 30 × 6.5 in	500 lb (250 kg)	191 lb	Consult				
33069	30 × 30 × 6.5 in	1,000 lb (500 kg)	191 lb	Consult				
33139	30 × 30 × 6.5 in	1,500 lb (750 kg)	191 lb	Consult				
33070	30 × 30 × 8.25 in	2,000 lb (1,000 kg)	281 lb	Consult				
33140	36 × 36 × 8.25 in	1,000 lb (500 kg)	234 lb	Consult				
33071	36 × 36 × 8.25 in	2,000 lb (1,000 kg)	234 lb	Consult				
33072	36 × 36 in × 8.25 in	5,000 lb (2,500 kg)	234 lb	Consult				
33141	38 × 46 × 8.25 in	1,000 lb (500 kg)	610 lb	Consult				
113569	38 × 46 × 8.25 in	2,000 lb (1,000 kg)	610 lb	Consult				
113570	38 × 46 × 8.25 in	5,000 lb (2,500 kg)	610 lb	Consult				
113572	48 × 48 × 8.25 in	1,000 lb (500 kg)	654 lb	Consult				
33073	48 × 48 × 8.25 in	2,000 lb (1,000 kg)	654 lb	Consult				
33074	48 × 48 × 8.25 in	5,000 lb (2,500 kg)	654lb	Consult				
33075	48 × 48 × 9.25 in	10,000 lb (5,000 kg)	735 lb	Consult				
33078	48 × 60 × 9.25 in	10,000 lb (5,000 kg)	845 lb	Consult				
33149	48 × 72 × 9.25 in	5,000 lb (2,500 kg)	1,120 lb	Consult				
33080	48 × 72 × 9.25 in	10,000 lb (5,000 kg)	1,120 lb	Consult				
33081	60 × 60 × 8.25 in	5,000 lb (2,500 kg)	967 lb	Consult				
33082	60 × 60 × 9.25 in	10,000 lb (5,000 kg)	1,180 lb	Consult				
33083	60 × 72 × 10.25 in	10,000 lb (5,000 kg)	-	Consult				
Stainless St	teel							
113581	24 × 24 × 6.5 in	500 lb (250 kg)	151 lb	Consult				
113582	24 × 24 × 6.5 in	1,000 lb (500 kg)	151 lb	Consult				
113586	30 × 30 × 8.25 in	2,000 lb (1,000 kg)	281 lb	Consult				
113588	36 × 36 × 8.25 in	2,000 lb (1,000 kg)	450 lb	Consult				
113595	48 × 48 × 8.25 in	5,000 lb (2,500 kg)	630 lb	Consult				
113604	48 × 60 × 8.25 in	5,000 lb (2,500 kg)	-	Consult				
113596	48 × 48 × 11.25 in	10,000 lb (5,000 kg)	735 lb	Consult				
113613	60 × 72 × 11.25 in	10,000 lb (5,000 kg)	1,290 lb	Consult				

Options/Accessories

- In the second					
Part #	Description	Price			
Consult	FXB forklift skid, constructed with (2) 8 in wide painted steel channels attached to FXB scale frame per customer's specified center-to-center distance Note: For FXB-3846 through FXB-6084 scales only	Consult			
Consult	FXB forklift skid with indicator column, constructed with (2) 8 in wide painted steel channels attached to FXB scale frame per customer's specified center-to-center distance, one channel extended beyond frame 12 in with 54 in indicator column Note: For FXB-3846 through FXB-6084 scales only	Consult			

NOTE: Indicator stand works with 120/120 Plus, 480/480 Plus, 482/482 Plus, 880/880 Plus, 882IS/882IS Plus, 882IS/882IS Plus w/battery, 680 Synergy

Si	tainless Steel		,		
•	Unique flexure	design	filters	motion	and

• Rugged all-steel painted construction

- shock loading
- All 304 stainless steel construction, smooth deck

• One RL20000 series nickel-plated s-beam load

• NTEP Certified models in sizes 24 × 24 in (500 lb) through 72×96 in up to 10,000 lb capacity

- Stainless flexures, hardware and load cell
- NTEP Certified models in sizes 24 × 24 in (500 lb) through 72×96 in up to 10,000 lb capacity

Specifications

End Loading Capacity:

100% of scale capacity

Safe Overload Capacity:

150% of scale capacity

Warranty:

Two-year limited

Approvals:

Painted: NTEP 88-100, Class III 5,000 d Stainless steel: NTEP 88-100, Class III 3,000 d

On rectangular scales, the forks MUST run the long direction of the scale so the cord grip will be on the side adjacent



