

# Intercom Kiosk



## Standard Features

- Moisture and puncture resistant speaker
- Three-layer steel baffle protects speaker from tampering
- Hands-free communication
- Weather and vandal resistant
- FRP enclosure

## Specifications

### Wiring:

CAT5 to Ethernet adapter

### Dimensions:

(L x W x H)

14 x 12 x 8 in

(355 x 304 x 203 mm)

### Communication:

PC software functions as base station for networked intercom system

TalkMaster™ FOCUS, download directly from

[www.digitalacoustics.com/talkmaster-focus-software-download/](http://www.digitalacoustics.com/talkmaster-focus-software-download/)

## Part Number/Price

| Part#  | Description       | Price   |
|--------|-------------------|---------|
| 215451 | Ethernet intercom | Consult |

# Network Cameras



License Plate Recognition



Remote Monitoring

## Remote Monitoring Specifications

### Read Range:

10 to 82 ft (3 to 25 m)

### Interface:

10 Base-T/100 Base TX Ethernet (RJ-45)

### Operating System:

Microsoft Windows® 10/8/7

### Web Browser:

Chrome 58 or above, Internet Explorer 10/11

### Power Input:

IEEE 802.3af PoE Class 0 (Power Redundancy)

### Power Consumption:

PoE: Max. 10.77/7.77 W (IR on/off)

### Night Illumination Range:

164 to 328 ft (50 to 100 m) with Smart IR II

### Dimensions:

5.75 x 11.34 in (146 x 288 mm)

### Temperature:

Operating:  
IR off: -40 °F to 140 °F (-40 °C to 60 °C)  
IR on: -40 °F to 122 °F (-40 °C to 50 °C)

### Weight (including bracket):

3.5 lb (1.6 kg)

### Rating:

IP66

### Approvals:

CE  
BIS  
FCC Class A

## License Plate Recognition Specifications

### Read Range:

10 to 82 ft (3 to 25 m)

### Image Sensor:

2 megapixels

1/2.8 in CMOS sensor

### Frame Rate:

25 FPS

### Interface:

LAN (weatherproof standard RJ-45)

10/100 Mbps

Ethernet interface Wi-Fi (for easy setup)

Relay control (1 input, 2 outputs)

Wiegand

### Power Input/Network:

24 to 48 V DC, PoE+ IEEE 802.3 at

Requires CAT 5e or better network, POE+ network switch or 24 to 48 VDC power supply

### Power Consumption:

Average 18 W, max 25 W

### Dimensions:

4.0 x 7.0 x 11.5 in

(102 x 180 x 290 mm)

### Weight:

6.5 lb (2.95 kg)

### Rating:

IP66

### Temperature:

Operating:  
-40 °F to 140 °F (-40 °C to +60 °C)

### Humidity:

0% to 95% RH

### Approvals:

IEC 62368-1, Electrical Safety General  
IEC 60950-22, Electrical Safety Outdoor

IEC 62471, Photobiological

EN 55022:2010, Emissions

EN 55024:2010, Immunity

IEC 60068-2-27 Ea, Shock

IEC 60068-2-64 Fh, Vibration

UL94 HB, Flammability

RoHS directive 2002/95/EC and RoHS2 directive 2011/65/EU

## Part Number/Price

| Part #                                  | Description   | Price   |
|---|---|---------|
| <b>Remote Monitoring Camera</b>         |   |         |
| 163175                                  | Ethernet camera 2-megapixel CMOS sensor   | Consult |
| 131605                                  | Power supply, POE injector, power cord not included   | Consult |
| 15438                                   | Power cord  | Consult |
| <b>License Plate Recognition Camera</b> |   |         |
| 220688                                  | Camera, LPR License Plate Recognition, requires CAT 5e or better network, POE+ network switch or 24-48VDC power supply. | Consult |
| 220690                                  | Mounting bracket, LPR Camera. Universal mounting bracket for license plate recognition camera.                          | Consult |
| 220691                                  | Cable power & relay LPR camera power cable  | Consult |