



350-10-8S

DIGITAL STRETCHER SCALE

The Rice Lake 350-10-8S digital stretcher scale is designed to be the first line of weighing when a patient is being received into a medical facility by a stretcher. The heavy-duty frame and wide ramps enable easy, safe and fast patient processing. Two rubber wheels allow easy and quiet transportation of the scale if needed. Advanced movement compensation technology eliminates involuntary movement made during the weighing process ensuring exact weighing information.



- Push-button LCD display
- Antimicrobial keypad
- Two wheels for portability
- Dual ramp
- Metal, nonslip platform
- Safety side rails
- Motiontrap™ movement compensation technology
- Unit of measure toggle or locking

- EMR capable
- Serial and USB data communication ports
- Bluetooth® BLE 4.0 available, part number selectable
- Tare function
- Hold function
- BMI (body mass index) function
- Factory calibrated



SPECIFICATIONS

Capacity:

 $1,000 \times 0.2 \text{ lb } (450 \times 0.1 \text{ kg})$

Platform Dimensions Without Ramps:

 $(L \times W \times H)$

 $49.30 \times 32.70 \times 2.60$ in

Platform Dimensions with Wheels and Ramps:

 $(L \times W \times H)$

 $63.80 \times 32.70 \times 2.60$ in

Power:

9 VDC, provided by six AA alkaline batteries (included) or AC adapter (optional)

Battery Type:

Six AA alkaline (included)

Battery Use:

25 hours continuous use with batteries Automatic power-off can be configured

Display:

5-digit LCD display, 0.75 in (1.9 cm) digit height

Temperature:

Operating:

50 °F to 104 °F (10 °C to 40 °C)

Cable Length:

7 ft (2.1 m) cable between scale base and indicator

Warranty:

Two-year limited





STRETCHER SCALE

| MODEL | CAPACITY | COMMUNICATION | PART# |
|--------------|--|--------------------|--------|
| 350-10-8S | $1,000 \times 0.2 \text{ lb } (450 \times 0.1 \text{ kg})$ | USB | 203622 |
| 350-10-8SBLE | 1,000 × 0.2 lb (450 × 0.1 kg) | Bluetooth® BLE 4.0 | 203623 |

OPTIONS

| DESCRIPTION | PART# |
|--|--------|
| 9 VDC adapter, 120 V/230 V auto switching* | 133077 |
| 9 VDC adapter, 230 V** | 102508 |
| Epson TM-U220 tape printer | 81076 |
| Cable, RS232 scale to printer, 6 ft, 25-pin D-Sub (male) to RJ45 | 186830 |
| Cable, USB 6 ft USB-A (male) to USB-B (male) | 79074 |
| Cable, Communication DB9 (female) to RJ45 (male), 4 conductor | 217091 |

SHIPPING WEIGHT

| MODEL# | PART# | L (IN) | W (IN) | H (IN) | PACKAGE WGT. (LB) | DIM WGT. (LB) | SHIPPING WGT. (LB) |
|--------------|--------|--------|--------|--------|----------------------|------------------|-----------------------|
| 350-10-8S | 203622 | 67.2 | 36 | 6 | 154 | 104 | 154 |
| 350-10-8SBLE | 203623 | 67.2 | 36 | 6 | 154 | 104 | 154 |

DIMENSIONS

| | INCHES | CENTIMETERS | | INCHES | CENTIMETERS |
|---|--------|-------------|---|--------|-------------|
| A | 63.80 | 162.1 | E | 3.90 | 9.9 |
| В | 49.30 | 125.2 | F | 2.60 | 6.7 |
| C | 32.70 | 83.1 | G | 0.55 | 1.4 |
| D | 32.90 | 83.6 | | | |














An ISO 9001 Registered Company ©2026 Rice Lake Weighing Systems 01/26 Specifications subject to change without notice. Visit ricelake.com