




Picture is a representation of actual product

### Order Information

Load Rating	Part #	Est. Weight	Price
20,000 kg	169233	10 lb	Consult
30,000 kg	169234	10 lb	Consult
50,000 kg	169235	13 lb	Consult

### Dimensions

Rated Capacity	A	B	C	D	E	F	O	R1	R2
kg/mm									
20,000	138.3	112.3	72.3	50.0	32.3	69.0	88.0	15.0	150.0
30,000	138.3	112.3	72.3	50.0	32.3	69.0	88.0	15.0	150.0
50,000	155.5	115.8	74.0	50.0	32.3	69.0	88.0	35.0	300.0



### Specifications

- Full Scale Output:**  
1.5 mV/V
- Output Resistance:**  
605 (± 5) ohm
- Input Resistance:**  
670 (± 15) ohm
- Material/Finish:**  
Stainless steel
- Temperature:**  
Operating:  
-0 °F to 150 °F (-18 °C to 65 °C)
- Seal Type:**  
Environmentally sealed, IP68
- Safe Overload:**  
150% full scale
- Rated Excitation:**  
5 to 10 VDC
- Combined Error:**  
0.02% of applied load
- Insulation Resistance:**  
2,000 megohm
- Cable Length:**  
15 m
- Cable Color Code:**  
Green +Excitation  
Black -Excitation  
Red +Signal  
White -Signal  
Blue +Sense  
Brown -Sense
- Warranty:**  
One-year limited

VPC®  
TEDEA-HUNTLEIGH®