

Part Number/Price

Part #	Model #	Capacity	Price
Consult	Rice Lake VS-20	550 × 0.2 lb (250 kg × 0.1 kg) with USB	Consult

Shipping Weight

Part #	Model #	L (in)	W (in)	H (in)	Package Wgt. (lb)	Dim Wgt. (lb)	Shipping Wgt. (lb)
Consult	Rice Lake VS-20	13	22	15	25	37	37

Options/Accessories


Part #	Description	Price
133077 [†]	9 VDC adapter, 100 to 240 VAC, 50/60 Hz auto-switching	Consult



† NEMA 1-15 Plug

Dimensions

	Inches	Centimeters
Α	12.70	32.3
В	22.40	56.9
С	14.70	37.4
D	3.00	7.6



Standard Features

- Push-button LCD display
- Large, stable scale base
- Nonslip rubber mat, removable for cleaning
- Antimicrobial keypad
- Unit of measure toggle or locking
- Motiontrap™ movement compensation technology
- USB communication
- · Hold function
- Tare function
- · Factory calibrated

Specifications

Capacity: 550 × 0.2 lb (250 × 0.1 kg)

Platform Dimensions:

(L × W × H) 14.70 × 14.70 × 3.00 in

Power:

9 VDC, provided by six AA alkaline batteries (included) or AC adapter (optional)

Battery Type:

Six AA alkaline (included)

Battery Use:

25 hours continuous use with batteries Automatic power-off can be configured

Temperature:

Operating: 50 °F to 104 °F (10 °C to 40 °C)

Display:

Five-digit LCD display, 0.75 in (1.9 cm) digit height

Two-year limited