

311M

MEDIUM TO HEAVY CAPACITY BELTSCALE





www.ricelake.eu

# 311M

## MEDIUM TO HEAVY CAPACITY BELTSCALE



Belt scale model 311M is suitable for most belt widths, applications and constructions (with both idler stations and flat rollers).

This model can be used for approved applications and is also available for ATEX categories II2D and II3D (zone 21 and 22)

## **Standard Features**

- Minimum modification to conveyor are required
- · Service friendly
- No moving parts
- Fits standard conveyors mounts with four bolts

### Weighframe, model 311M

Construction: Weigh frame without moving parts, which is mounted across the stringers of the belt conveyor. On the top part

across the stringers of the belt conveyor. On the top part one idler set is placed. In between the two parts of the

frame, one load cell is mounted.

Mounting: The weighframe fits in any kind of standard conveyor

and is assembled in our factory in one piece, so it can be mounted with only four bolts to the conveyor.

Finishing: Powder coating, colour RAL 3020.

According to procedure: 
• Shot blasting SA 2.5

• One layer epoxy powder coating, weather proof type

• Thickness minimum 80 µm

## **Load Cells, Single Point**

Type loadcell: Single point Construction: IP68
Material: SS

#### **Electronics**

See applicable datasheet.



NL-6666 MH Heteren - The Netherlands
Tel: +31 (0) 26 472 1319 | Email: europe@ricelake.com
www.ricelake.com

Rice Lake, Wisconsin 54868 - USA

Tel: (715) 234 9171 | Fax: (715) 234 6967