



## DIRECT THERMAL STAINLESS STEEL LABEL PRINTER

The SURVIVOR® SST3® is the first printer of its kind to achieve an IP69K rating. The ergonomically designed stainless steel cover completely seals out moisture and humidity, making it the only choice for washdown settings. This latest addition to the SST family adds faster processing speed, enhanced onboard memory, printer emulation, and more connectivity options than ever before. See what the SST3 has to offer. We think you're really going to like what you find.

**RICE LAKE**  
WEIGHING SYSTEMS  
To be the best by every measure®

230 W. Coleman St. • Rice Lake, WI 54868 • USA  
TEL: 715-234-9171 • FAX: 715-234-6967  
[www.ricelake.com](http://www.ricelake.com)

An ISO 9001 registered company  
© 2014 Rice Lake Weighing Systems PN 111130 1/14  
Specifications subject to change without notice

## Rice Lake SST Matrix

	<b>SST3</b>	<b>SST2</b>	<b>SST</b>
<b>Enclosure</b>	304 stainless steel	304 stainless steel	304 stainless steel
<b>Warranty</b>	One-year	One-year	One-year
<b>Print Speed</b>	10ips	8ips	6ips
<b>Printhead Resolution</b>	203 dpi Optional 300 dpi	203 dpi	203 dpi
<b>Printhead</b>	IntelliSEQ™*	Standard	Standard
<b>Max Print Width</b>	4.25in (107.9mm)	4.09in (103.8mm)	4.1 in (104.1 mm)
<b>Max Print Length</b>	99in (2,514.6mm)	99in (2,514.6mm)	10in (254mm)
<b>Max Media Width</b>	4.65in (118.1 mm)	4.65in (118.1 mm)	4.6in (116.8mm)
<b>Max OD Media</b>	8.0in (203.2mm)	8.0in (203.2mm)	8.0in (203.2mm)
<b>Label Position Sensing</b>	Auto	Manual	Manual
<b>Printer Base Unit</b>	M-4210 Mark II	I-Class 4208	Prodigy Plus
<b>Printer Emulations</b>	Prodigy/Prodigy Plus/Allegro	Prodigy/Prodigy Plus/Allegro	N/A
<b>Processor</b>	150MHZ	66MHZ	—
<b>Memory</b>	16MB RAM/8MB Flash	8MB RAM/1MB Flash	256KB
<b>Real Time Clock</b>	Standard	N/A	N/A
<b>Internal Structure</b>	Die-cast aluminum frame	Die-cast aluminum frame	Sheet metal
<b>Interfacing</b>	Parallel, USB and RS-232 onboard	Parallel, RS-232 onboard	Parallel or RS-232
<b>Components</b>	Internal rewind, peel and present standard	Options	Internal rewind standard
<b>Washdown Protection</b>	NEMA 4X, IP69K	NEMA 4X	NEMA 4X
<b>Options Configuration</b>	Field installable auto sensing	Field installable	Factory installed only
<b>Options</b>	Ethernet, Wi-Fi Heater Thermal Transfer	Ethernet Heater Thermal Transfer	N/A N/A N/A

\*The IntelliSEQ (Intelligent Sequential Energy Adjustment for Quality) printhead contains a secured memory device that stores pertinent data about the electrical profile of the printhead as well as user operational data. IntelliSEQ monitors, adjusts, and controls essential printhead functions. A PC-based software application extracts the information, imports it into an easy-to-read template which is displayed to the user.