



Part Number/Price

Part #	Capacity	Est. Weight	Price
154835	500 g (1 lb)	8 lb (3.5 kg)	Consult
154836	1 kg (2 lb)	8 lb (3.5 kg)	Consult
154838	2.5 kg (5 lb)	11 lb (5 kg)	Consult
154839	5 kg (10 lb)	11 lb (5 kg)	Consult
154840	10 kg (20 lb)	11 lb (5 kg)	Consult
154841	25 kg (50 lb)	11 lb (5 kg)	Consult

Standard Features

- Stainless steel platter
- ABS injection-molded plastic base
- Single-point strain gauge load cell
- Adjustable legs
- Leveling bubble
- 14-pin connector on three-meter cable

Specifications

Output Impedance:

350 \pm 5 ohm

Insulation Resistance:

> 500 megohm

Rated Output:

1.0016 mV/V

Load Cell Type:

K-Type cell

Load Cell Cable Length:

118 in (3 m)

Load Cell Color Code:

Green +Output
Yellow -Output
Black Shield
White -Input
Red +Input

Temperature:

Operating:
14 °F to 104 °F (-10 °C to 40 °C)

Dimensions:

13.4 \times 11.1 \times 3.5 in
(341 \times 284 \times 90 mm)

Platter Dimensions:

500 g: 7.9 \times 5.6 in (201 \times 143 mm)
1 kg: 9.6 \times 6.9 in (244 \times 177 mm)
2.5 to 25 kg: 13.4 \times 11.1 in (341 \times 284 mm)

Warranty:

Three-year limited