

RoughDeck® SLV



LEGAL
FOR TRADE



RICE LAKE®
WEIGHING SYSTEMS


800-472-6703
www.ricelake.com

RoughDeck® SLV

The SLV offers the rugged and durable features of a RoughDeck floor scale modified to meet the demands of livestock weighing. The diamond tread plate and rigid structural steel channel frame provide durability for weighing sheep, goats, cattle, hogs, horses and more. The SLV can be customized for retrofit or unique applications.

Accuracy requires a specialized foot

Adjustable SUREFOOT™ support feet incorporate stainless steel top plates and neoprene bases. This unique combination decreases extraneous forces on the load cell, resulting in superior accuracy and repeatability.



380 Synergy Series

The 380 Synergy Series digital weight indicator is battery powered, providing up to 100 hours of continuous use. Four C-cell batteries can be easily replaced through bottom access caps, and an optional AC power supply is available to satisfy a range of preferences. The bright, six-digit LCD display makes it easy for operators to read individual animal weights.

The stainless steel, IP66-enclosed 380 Synergy ensures the device is dust-tight and withstands high-pressure water, making it ideal for use on ranches and farms. The 380 Synergy has an easy-to-use keypad and can be paired with a printer to quickly and efficiently track animal weight readouts.



Drawing is a representation of PN 226207 SLV scale

STANDARD FEATURES

- Mild steel construction
- Diamond safety tread plate deck
- Rigid-type structural steel channel frame
- NEMA Type 4X, stainless steel side-access junction box without quick connector
- Signal trim summing board
- Four adjustable stainless steel SUREFOOT support feet
- SURVIVOR® EL147HE hostile environment load cell cable
- Four alloy steel load cells

OPTIONS

- Smooth deck
- Rubber mat
- Stainless steel load cells (RL32018S IP66) and hardware
- Stainless steel hermetically sealed load cells (RL32218S-HE IP69K) and hardware
- Angle iron bolted to scale for wood deck provisions

(Note: wood to be supplied by customer)

SPECIFICATIONS

END LOAD CAPACITY:	125% full scale
CABLE LENGTH:	20 ft (6 m)
CAPACITY:	Not to exceed 4,000 lb × 1 lb (32 square feet) 3 ft × 8 ft: 4,000 lb × 1 lb increments 4 ft × 8 ft: 4,000 lb × 1 lb increments
APPROVALS:	NTEP CC 92-001 Class III 4,000 d
WARRANTY:	Two-year limited (scale only)

APPROVALS



Drawing is a representation of PN 226206 SLV scale