

# **Spherical Washer Sets**

## Weldless End Links



#### Part Number/Price

Part#	Bolt Size	A	В	С	D	Price		
Mild Stee								
15196	0.25 in	0.62 in	0.20 in	0.28 in	0.31 in	Consult		
15197	0.38 in	0.88 in	0.25 in	0.41 in	0.44 in	Consult		
15198	0.50 in	1.12 in	0.31 in	0.53 in	0.56 in	Consult		
15199	0.62 in	1.38 in	0.31 in	0.66 in	0.69 in	Consult		
15200	0.75 in	1.62 in	0.38 in	0.78 in	0.81 in	Consult		
15201	1.00 in	2.00 in	0.50 in	1.06 in	1.12 in	Consult		
15202	1.25 in	2.62 in	0.50 in	1.31 in	1.38 in	Consult		
15203	1.50 in	2.88 in	0.53 in	1.56 in	1.62 in	Consult		
15205	2.00 in	3.88 in	0.81 in	2.06 in	2.12 in	Consult		
Stainless Steel								
33218	0.50 in	1.12 in	0.31 in	0.53 in	0.56 in	Consult		
33220	0.75 in	1.62 in	0.38 in	0.78 in	0.81 in	Consult		



### **Standard Features**

- Self-colored or hot-dip galvanized finish
- Forged carbon steel quenched and tempered

### Part Number/Price

Part#	A	В	С	D	Safe Load*	Price
F312L	0.625 in	1.00 in	3.25 in	2.32 in	9,300 lb	Consult
17810	0.875 in	2.00 in	5.13 in	3.75 in	12,000 lb	Consult
21911	1.00 in	2.25 in	5.75 in	4.25 in	15,200 lb	Consult
65430	1.25 in	2.50 in	7.00 in	5.00 in	26,400 lb	Consult
21912	1.375 in	2.75 in	7.75 in	5.50 in	30,000 lb	Consult

<sup>\*</sup>Do not exceed the safe load

# **Load Cell Spacers**

## **Load Button**




### **Standard Features**

- Use with most popular single-ended beams
- Provides flat mounting surface required for optimal load cell performance
- Zinc-plated mild steel or stainless steel

### Part Number/Price

Part#	С	Н	H1	L	L1	L2	W	Price	
Mild Steel									
17754	0.53 in	1.25 in	0.62 in	2.25 in	0.62 in	1.00 in	0.25 in	Consult	
17755	0.78 in	1.50 in	0.75 in	3.00 in	0.75 in	1.50 in	0.25 in	Consult	
17756	1.03 in	2.00 in	1.00 in	4.00 in	1.00 in	2.00 in	0.25 in	Consult	
18260	0.53 in	1.25 in	0.62 in	2.25 in	0.62 in	1.00 in	0.37 in	Consult	
Stainless Steel									
17757	0.78 in	1.50 in	0.75 in	3.00 in	0.75 in	1.50 in	0.25 in	Consult	
18383	0.53 in	1.25 in	0.62 in	2.25 in	0.62 in	1.00 in	0.37 in	Consult	
18411	0.53 in	1.25 in	0.62 in	2.25 in	0.62 in	1.00 in	0.25 in	Consult	





### **Standard Features**

### **Load Button**

- Suitable for use with compression mounting assemblies, canisters, S-beams and single-ended beams
- · Hardened alloy steel

#### Part Number/Price

Part#	T	D	Н	H1	R	W	Price
17750	3/8-24 UNF	0.75 in	0.60 in	0.30 in	2.00 in	0.63 in	Consult
17751	1/2-20 UNF	0.75 in	0.70 in	0.30 in	4.00 in	0.63 in	Consult
17752	3/4-16 UNF	1.50 in	0.90 in	0.30 in	6.00 in	1.25 in	Consult

