# 220 Universal Mount

Stainless Steel, Weigh Module Kit, VPG® Tedea-Huntleigh®



## Complete Kit Includes

- Three or four 220 stainless steel compression mounts with 220 stainless steel hermetically sealed compression disk load cells
- One JB4SS NEMA Type 4X stainless steel signal trim junction box
- 25 ft of hostile environment EL147HE SURVIVOR® load cell cable

## **Standard Features**

- Capacities (per module): 5,000 to 30,000 kg
- mV/V/ohm calibrated load cells eliminates the need for trimming
- · Stainless steel construction
- Easy load cell replacement
- Integral jacking/shipping bolts

### **Applications**

- Medium- to high-capacity tanks, bins and hoppers
- Washdown or corrosive applications
- Process control and batch weighing

#### **Order Information**

Load Rating (Per Module)	Part#	Price						
3-Module Kit (Includes Load Cell)								
5,000 kg	66208	Consult						
10,000 kg	66209	Consult						
20,000 kg	66210	Consult						
30,000 kg	66211	Consult						
4-Module Kit (Includes Load Cell)								
5,000 kg	66212	Consult						
10,000 kg	66213	Consult						
20,000 kg	66214	Consult						
30,000 kg	66215	Consult						

### **Replacement Mount Parts**

Load Rating (Per Module)	Part#	Price
Saddle 5,000 to 10,000 kg	227786	Consult
Rolling cylinder 5,000 to 10,000 kg	170882	Consult
Load adapter 5,000 kg	170880	Consult
Load adapter 10,000 kg	170881	Consult
Rubber boot 5,000 to 10,000 kg	171211	Consult
Saddle 20,000 to 30,000 kg	170884	Consult
Rolling cylinder 5,000 to 10,000 kg	170885	Consult
Load adapter 5,000 to 10,000 kg	170883	Consult
Rubber boot 5,000 to 10,000 kg	171212	Consult

#### **Dimensions**

Rated Capacity	A	В	С	D	E	Н	I	J	K
5,000 to 10,000	127.0	203.0	90.0	170.0	18.0	107.0	Load Cell Replacement Height: 118.0 Operating Height: 107.0	19.1	25.4
20,000 to 30,000	152.0	245.0	115.0	208.0	24.0	148.0	Load Cell Replacement Height: 156.0 Operating Height: 148.1	31.8	25.4



