



Part Number/Price

Part #	Description	Est. Weight	Price
With 380 I	ndicator		
2,500 lb C	apacity		
214517	2,500U 22 – Farm Bar kit, 22 in with 380, 2,500 capacity, square pads	98 lb	Consult
5,000 lb C	apacity		
214518	5,000U 26 – Farm Bar kit, 26 in with 380, 5,000 capacity, square pads	117 lb	Consult
214519	5,000U 33 – Farm Bar kit, 33 in with 380, 5,000 capacity, square pads	123 lb	Consult
214520	5,000U 36 – Farm Bar kit, 36 in with 380, 5,000 capacity, square pads	128 lb	Consult
214521	5,000U 40 – Farm Bar kit, 40 in with 380, 5,000 capacity, square pads	134 lb	Consult
214522	5,000U 44 – Farm Bar kit, 44 in with 380, 5,000 capacity, square pads	140 lb	Consult
214523	5,000U 48 – Farm Bar kit, 48 in with 380, 5,000 capacity, square pads	146 lb	Consult
10,000 lb	Capacity		
214524	10,000U 32 – Farm Bar kit, 32 in with 380, 10,000 capacity, square pads	152 lb	Consult
214525	10,000U 36 – Farm Bar kit, 36 in with 380, 10,000 capacity, square pads	152 lb	Consult
214526	10,000U 48 – Farm Bar kit, 48 in with 380, 10,000 capacity, square pads	175 lb	Consult
214527	10,000U 60 – Farm Bar kit, 60 in with 380, 10,000 capacity, square pads	210 lb	Consult
214528	10,000U 72 – Farm Bar kit, 72 in with 380, 10,000 capacity, square pads	230 lb	Consult

Options/Accessories

Part #	Description	Price
159788	Extension cable, farm bar, 10 ft long	Consult
127556	Homerun cable, 12ft long, 4-pin male to blunt end, for indicator	Consult
202711	380 indicator	Consult
206433	Power supply, 12V 6W	Consult
23113	Printer TM-U295	Consult
71630	Scale tickets, 500/pack	Consult
15547	Blunt end to DB25, RS-232 cable for printer to indicator	Consult

Standard Features

- Indicator cable length 12 ft
- 3 ft ArmorGuard cable included
- Kit includes 380 Synergy Series digital weight indicator powered by 4 C-cell batteries (not included)
- Factory calibrated when sold with instrumentation
- Capacities from 2,500 to 10,000 lb
- · Non-Legal for Trade

Farm Bar Specifications

Safe Overload:

150%

Full Scale Output:

3mv/V nominal

Output is standardized for each model of load bar, consult factory for details

Maximum Excitation:

15 VDC

Nonlinearity:

0.02% full scale

Husteresis:

0.02% full scale

Bridge Resistance:

350 ohm

Temperature Range:-40 °F to 111 °F (-40 °C to 44 °C)

Cable Configuration:

8 ft between bars and 12 ft for the indicator

Two-year limited

380 Specifications

Batteries: 4 alkaline C-cell (not included) Optional: 115/230 VAC to 12 VDC adapter

Battery Life:

100 hours wwith 1 × 350 ohm load cell, no backlight

Communication Ports:

One RS-232 (three-wire)

One USB 2.0

Annunciators:

g, lb, t, tn, kg, oz, battery level, PT, LT, gross, zero, unstable, net

Display: Six 1 in (25 mm) tall, LCD digits

Keys/Buttons: 5 tactile buttons

Rating/Material:

IP66

Stainless steel

Approvals:

NTEP 21-051

Measurement Canada AM-6184

cULus

Farm Bars

Without Instrumentation



Part Number/Price

Part #	Description	Est. Weight	Price				
2,500 lb C	2,500 lb Capacity						
152016	2,500 lb 22 – Farm Bar set, with square pads	92 lb	Consult				
5,000 lb C	apacity						
152018	5,000 lb 26 – Farm Bar set, with square pads	111 lb	Consult				
152019	5,000 lb 33 – Farm Bar set, with square pads	117 lb	Consult				
152020	5,000 lb 36 — Farm Bar set, with square pads	122 lb	Consult				
152021	5,000 lb 40 – Farm Bar set, with square pads	128 lb	Consult				
152022	5,000 lb 44 — Farm Bar set, with square pads	134 lb	Consult				
152023	5,000 lb 48 – Farm Bar set, with square pads	140 lb	Consult				
10,000 lb Capacity							
185437	10,000 lb 32 – Farm Bar set, with square pads	146 lb	Consult				
152024	10,000 lb 36 – Farm Bar set, with square pads	146 lb	Consult				
152025	10,000 lb 48 – Farm Bar set, with square pads	169 lb	Consult				
152026	10,000 lb 60 — Farm Bar set, with square pads	204 lb	Consult				
152027	10,000 lb 72 – Farm Bar set, with square pads	224 lb	Consult				

Options/Accessories

Part #	Description	Price
159788	Extension cable, farm bar, 10 ft long	Consult
127556	Homerun cable, 12 ft long, 4-pin male to blunt end, for indicator	Consult
202711	380 indicator	Consult
23113	Printer TM-U295	Consult
71630	Scale tickets, 500/pack	Consult
15547	Blunt end to DB25, RS-232 cable for printer to indicator	Consult

Standard Features

- 3 ft ArmorGuard cable included
- Capacities from 2,500 to 10,000 lb
- Non-Legal for Trade

Specifications

Safe Overload:

Full Scale Output:

3mv/V nominal

Output is standardized for each model of load bar, consult factory for details

Maximum Excitation:

15 VDC

Nonlinearity:

0.02% full scale

Hysteresis:

0.02% full scale

Bridge Resistance:

350 ohm

Temperature Range:-40 °F to 111 °F (-40 °C to 44 °C)

Cable Configuration:

8 ft between bars and 12 ft for the indicator

Warranty:

Two-year limited



Dimensions

Farm Bar 2,500U					
Α	В	С	D	E	
22 00 in	15 00 in	19 75 in	25 75 in	4 00 in	

Farm Bar 5,000U					
Α	В	С	D	E	
26.00 in	19.00 in	23.75 in	29.75 in	4.00 in	
33.00 in	26.00 in	30.75 in	36.75 in	4.00 in	
36.00 in	29.00 in	33.75 in	39.75 in	4.00 in	
40.00 in	33.00 in	37.75 in	43.75 in	4.00 in	
44.00 in	37.00 in	41.75 in	47.75 in	4.00 in	
48.00 in	41.00 in	45.75 in	51.75 in	4.00 in	

Farm Bar 10,000U					
A	В	С	D	E	
32.00 in	25.00 in	29.75 in	35.75 in	4.00 in	
36.00 in	29.00 in	33.75 in	39.75 in	4.00 in	
48.00 in	41.00 in	45.75 in	51.75 in	4.00 in	
60.00 in	53.00 in	57.75 in	63.75 in	4.00 in	
72.00 in	65.00 in	69.75 in	75.75 in	4.00 in	
	65.00 in		1	4.00 in	

- * B equals dimension A less 7 inches
- * D equals dimension C plus 6 inches

