

Part Number/Price

Part #	Size (W × L × H)	Capacity	Est. Weight	Price
RoughDeo	k EQ Floor Scale with 482 Indicato	r		
207811	4 ft × 6 ft × 4.25 in	2,500 × 0.5 lb	610 lb	Consult
Note: Heiaht	includes stall mat			

Options/Accessories

Part #	Description	Price
Consult	Access ramps	Consult list price add-on
Consult	Smooth deck instead of diamond safety tread plate	N/C
12839*	50 lb cast iron calibration weights	Consult
207812	Guide rail, 5.66 ft long \times 4.36 ft high, field installable, black matte finish	Consult list price add-on
18777	Floor anchor plates	Consult
Consult	Hermetically sealed load cells	Consult

*Quantity of 5 weights is recommended for 10% of capacity.



Equine Floor Scale and Indicator Package

Standard Features

- Package includes 4 ft × 6 ft × 4.25 in floor scale with stall mat, 20 ft of SURVIVOR EL147HE hostile environment load cell cable and indicator
- Mat thickness 0.75 in

Scale

- Heavy-duty design with structural steel channel frame
- Stall mat to reduce noise and instill equine comfort
- 4 adjustable stainless steel SUREFOOT™ support feet
- Powder-coated black matte finish

Indicator

- LCD backlit display for a variety of environments
- Battery backed time and date
- Communication ports for connecting to a variety
 of peripherals

RoughDeck EQ Specifications

End Load Capacity:

100% full scale at 2,500 lb

Load Cells: Model RL32018 alloy steel environmentally

sealed IP66

Junction Box:

Side access, TuffSeal JB4SS stainless steel, NEMA Type 4X with a signal card

Feet:

Stainless steel SUREFOOT, adjustable (+0.25 in or -0.125 in) for leveling the scale

Finish: Powder coat painted, black matte

Cable Length:

20 ft (6.1 m) for connecting scale junction box to indicator

Threaded Eyebolt:

One lifting hole located in center of scale for easy install (requires 1/2-20NF eyebolt, not included)

Warranty: Two-year limited

482 Specifications

Power:

Line voltages: 100 to 240 VAC Frequency: 50/60 Hz DC voltages: n/a

Communication Ports:

Com 1: RS-232 full duplex Com 2: RS-232 full duplex or 20 mA simplex, continuous

Both ports 1200, 2400, 4800, 9600, 19200, 38400 baud seven or eight data bits, even, odd or no parity

Optional Ethernet and USB Board:

USB five-pin header for PC, printer or flash drive Ethernet TCP/IP, RJ45 jack, server and client ports

Display:

LCD backlit, transmissive/ transflective, 0.8 in (20 mm), six-digit, seven-segment

Annunciators:

Gross, net, center of zero, standstill, lb, kg, tare, preset tare

Keys/Buttons:

Flat membrane panel, embossed keys, tactile feel **Rating/Material:**


NEMA Type 4X/IP66 Stainless steel

Approvals:

NTEP 12-123 Measurement Canada AM-5892C CE cULUS

www.ricelake.com | Phone: 800-472-6703 An ISO 9001:2015 Accredited Company ©2024 Rice Lake Weighing Systems 3/24 Prices and specifications subject to change without notice. Visit ricelake.com for current prices.

RoughDeck[®] EQ Equine Floor Scale and Indicator Package



20

LARGE ANIMAL SCALES

RICE LAKE⁶ An ISO 9001:2015 Accredited Company © 2024 Rice Lake Weighing Systems 3/24 Prices and specifications subject to change without notice. Visit ricelake.com for current prices.