

GoDEX® GX4000i Pro Series

Direct Thermal/Thermal Transfer Label Printer



Approvals



Standard Features

- Built in video assist guidance
- Free GoLabel and GoLabel II design software
- 32-bit RISC CPU
- Equipped with a 5 in LCD touchscreen
- Aluminum cast frame

Part Number/Price

Part #	Description	Est. Weight	Price
GX4200i			
222248	Printer, Label GX4200i, 203 dpi, 5 inch color touchscreen	30 lb	Consult
GX4300i			
222250	Printer, Label GX4300i, 300 dpi, 5 inch color touchscreen	30 lb	Consult

Options/Accessories

Part #	Description	Price
225332	Wi-Fi module	Consult
Label Stock/Ribbon (W × L)		
21776	Direct thermal, 3 × 3 in, 8 in diameter with perf., 2,000/roll	Consult/roll
150921	Direct thermal, 4 × 6 in, 6 in diameter with perf., 1,000/roll	Consult/roll
25975	Direct thermal, 4.25 × 2.5 in, 6 in diameter with perf., 1,095/roll	Consult/roll
21785	Thermal transfer, 2 × 1 in, 8 in diameter, 5,500/roll	Consult/roll
21788	Thermal transfer, 4 × 6 in, 8 in diameter, 1,000/roll	Consult/roll
20573	Thermal transfer, 4 × 6.5 in, 8 in diameter, 900/roll	Consult/roll
34056	Ribbon, black, 4 in, 1,181 ft, wax	Consult/roll
126629	Thermal kit, (4) 4 × 4 in labels, (2) 4 in ribbons and 1 cleaning card	Consult
Cables		
41276	DB9 male RS-232 serial data cable with blunt end (Rice Lake indicators)	Consult
64794	DB9 RS-232 serial data cable with DB9F to DB9M	Consult
37527	6 ft parallel cable	
79074	USB-A (male) to USB-B (male) cable, 6 ft	Consult
Printheads		
225309	Printhead, 203 dpi	Consult
225310	Printhead, 300 dpi	Consult

Specifications

Print Speed:

GX4200i: up to 16 ips
GX4300i: up to 12 ips

Print Width:

4.09 in

Print Length:

GX4200i: 0.16 to 279.53 in
GX4300i: 0.16 to 125.98 in

Media:

Types: Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
Thickness: Min. 0.0024 in - Max. 0.01 in
Label Roll Diameter: Max. 8 in
Core Diameter: Min. 1.5 in - Max. 3 in

Printer Language:

EZPL, GEPL, GZPL, GDPL auto switch

Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions
TTF fonts: (Bold / Italic / Underline) 0°, 90°, 180°, 270° rotatable
Internal TTF Fonts x 5: Traditional Chinese, Simplified Chinese, Japanese, Korean, Western languages

1-D Bar Codes:

China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128 (subset A, B, C), EAN-8/ EAN-13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5, Interleaved 2-of-5 (I 2 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT-128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-E (with 2 or 5 digit extension), UCC/EAN-128 K-Mart, Random Weight and Pharmacode

2-D Bar Codes:

Aztec code, Code 49, Codablock F, Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417, QR Code, TLC 39, GS1 Composite, DotCode, Marco PDF 417

Memory:

256 MB flash; 256 MB SDRAM

Interfaces:

USB 2.0 (Type B)
Serial Port (RS-232)
Ethernet 10/100 Mbps
USB Host (A-Type)

Power:

Auto Switching 100 to 240 VAC, 50/60 Hz

Resolution:

GX4200i: 203 dpi
GX4300i: 300 dpi

Temperature:

Operating: 41 °F to 104 °F (5 °C to 40 °C)
Storage: -4 °F to 140 °F (-20 °C to 60 °C)

Dimensions:

(L × W × H)
18 × 11 × 12 in
(460 × 269 × 309 mm)

Warranty:

Five-year limited

Approvals:

CE Listed
FCC Class B
cULus Listed