



# ASTA PRICE COMPUTING ELECTRONIC SYSTEM SCALE PRINTER





## **Precise Computing Performance**

Engineered for precision and consistency, the Ishida Astra II price computing scale with printer combines unmatched performance with an ergonomic design that enhances customer convenience. The Astra II incorporates bright, easy-to-read displays, an easy label loading feature and user-friendly keyboard design for enhanced user operation perfect for supermarkets, bakeries, c-stores, delis and more!

To speed setup, the Astra II features an optional software tool that allows quick PLU editing using a PC. In addition, the configuration parameters can be saved for safe backup. With memory storage of 2MB, the Astra II can store a large amount of PLUs, tares and extra messages, virtually ensuring that you will never run out of memory.

The Astra II produces eye-catching point-of-purchase labels up to 2.5 inches (64 mm) in width and 6.9 inches (175 mm) long—all at an incredibly fast 3.9 inches (100 mm) per second. With 84 one-touch preset keys and 168 presets, these programmable function keys allow for efficient transactions and ease-of-use for operators.



Astra II incorporates an easy label loading feature and produces eye-catching point-of-purchase labels..

#### **Standard Features**

- Print speed of 3.9 in (100 mm) per second
- · Convenient side-loading label feature
- TC/IP 10/100 Base T Ethernet
- Proportional tare
- 84 one-touch preset keys, 168 presets (assign two items/key 0)

### **Specifications**

**Capacity:** 30 lb x 0.01 lb (13608 g x 4.54 g)

Weighing Resolution:

3,000 display divisions maximum

Display Types:

LCD, blue alphanumeric (23 digits, 16 seg)

Display Items: Ta

Tare: Four-digits Unit price: Five-digits Total price: Six-digits

Preset Kevs:

84 one-touch preset keys 168 presets

(assign two items/key)

Memory Capacity: 2MB

Communications: TCP/IP 10/100 Base T Ethernet

**Platter:** 14.5 x 10.5 in

Printing Speed: 3.9 in (100 mm) per second

Printing: Direct thermal 2.2 in (56 mm) (448 dot, 8 dot/mm)

Label Size:

Width: 1.5-2.5 in (38-64 mm) {min} Length: 1.2-6.9 in (30-175 mm) {max}

Inside diameter: 1.6 in (40 mm) Outside diameter: 3.9 in (100 mm)

Label Backing

Paper:

Label Roll:

Width: Up to 2.6 in (66 mm)

Power Supply:

AC100-240 V, 50/60 Hz

Power

Consumption: Standby: 50 W; In operation: 100 W
Classification: NTEP CC 07-005; UL Listed

Warranty: One-year limited warranty

#### **Approval**







Astra II Display

Your Rice Lake Weighing Systems distributor is:

