

Standard Features • Wireless connection from scale to operator display · Works with any basic digital weight indicator • Excitation to the load cell(s) provided by the transmitter, not the indicator • Each transmitter/receiver set is individually paired and will not interfere with another set • Transmitter excitation voltage: +4.8 VDC, 16 × 350 ohm or 32 × 700 ohm load cells Scale is sold separately .38 in TOP OF FRAME TO TOP OF SCALE WITH SCALE FEET IN NOMINAL POSITION

Part Number/Price

Part #	Size (W × L)	Est. Weight	Price			
RoughDeck HP Caster Portability Frame						
210902	$2.5\times2.5\text{ft}$, up to 5,000 lb capacity, two rigid forged steel caster on front, two swivel forged steel caster on back with drawer for SENDit, frame only	315 lb	Consult			
210903	3×3 ft, up to 5,000 lb capacity, two rigid forged steel caster on front, two swivel forged steel caster on back with drawer for SENDit, frame only	330 lb	Consult			
210904	$4\times4\text{ft}$, up to 5,000 lb capacity, two rigid forged steel caster on front, two swivel forged steel caster on back with drawer for SENDit, frame only	355 lb	Consult			
210905	$4\times4\text{ft}$, up to 10,000 lb capacity, two rigid forged steel caster on front, two swivel forged steel caster on back with drawer for SENDit, frame only	355 lb	Consult			
SENDit Wireless Electronics Kit						
210898	SENDit wireless load cell interface kit, non-NTEP, indicator not included (customer to supply)	-	Consult			

Options/Accessories

Part #	Description	Price
162173	Battery, 6 V SLA	Consult

Dimensions

Scale Size	2.5 × 2.5 ft	3 × 3 ft	4 × 4 ft
Α	33.92 in	39.92 in	51.92 in
В	33.92 in	39.92 in	51.92 in
С	30.75 in	36.75 in	48.75 in
D	30.75 in	36.75 in	48.75 in

Note: 1 in=25.4 mm