

Ishida WIL-Acro II

Compact Label Printer



FEATURES

- Compact space-saving design fits almost anywhere
- Removable front-load cassette with seven cassette combinations and virtual function
- High-resolution printhead prints safe handling instructions, country of origin, 2020 nutrition, custom text messages, custom images and more
- Batch printing
- Dynamically generated QR code printing
- Customizable touchscreen with adjustable viewing angle with tactile keypad
- Assign color images to presets keys
- Display videos with sound on operator display
- PC-based with a solid state drive for speed and reliability
- Secure remote access
- Fully compliant with RoHS regulations for a completely lead-free machine
- Compatible with third-party software, including Upshop 360®, ADC's InterScale®, Invafresh's ePlum®, Toast®, Square® and Droste®



Label cassette

MULTI-PURPOSE
RETAIL SCALESPRICE COMPUTING
SCALESPRICE COMPUTING
PRINTING SCALES

LABELERS

WRAPPING
SYSTEMS

SOFTWARE

ACCESSORIES

POWER
CONDITIONINGRETAIL
LABELS

WARRANTY

SPECIFICATIONS

Power:
110 to 120 VAC, 50/60 Hz

Power Consumption:
In operation: 120 W
Stand-by: 50 W

Communications:
LAN
Static/DHCP
Optional Wi-Fi 802.11a/b/g/n/ac
2.4 GHz/5 GHz
Security: WEP/WPA/WPA2

Input/Output:
LAN
Four USB-A (service, transaction data)
SD card (for transaction data,
16 GB max)

Operating System:
Linux

Memory Capacity:
SSD 2 GB

Preset Keys:
99 dynamically programmed groups
with 99 sub pages
15 tactile function keys

Display:
Operator: Resistive thin film analogue
touch panel, TFT LCD color
touchscreen with LED backlight
with SVGA 8.4 in (800 × 600 px)
Unit price: six digits
Total price: eight digits

Printer:
Printhead: 3.1 in (80 mm)
direct thermal, effective 3 in (78 mm)
Resolution: 300 dpi (12 dot/mm)
Speed: 5.9 in/sec (150 mm/sec) max
Formats: customizable, up to 999
Barcode: UPC, JAN, EAN, EAN128,
CODE128, ITF, GS1, QR, Custom

Label Size:
Type: die-cut, continuous
Width: 1.5 to 3.1 in (38 to 80 mm)
Length: 1.2 to 7.9 in (30 to 200 mm)

Label Roll:
I.D.: 1.6-in (40 mm) min
O.D.: 3.9-in (100 mm) max
Backing width: 3.2-in (82 mm) max

Weight:
Approx. 26 lb (12 kg)

Temperature:
Operating: 23 °F to 104 °F
(-5 °C to 40 °C)

Humidity:
20 to 85% (without condensation)

Warranty:
One-year limited

Approvals:
cULus Listed



PART NUMBER/PRICE

| PART # | MODEL | WIRELESS | CAPACITY | EST. SHIP WEIGHT | PRICE |
|--------|-------------|----------|---------------|------------------|---------|
| 220068 | WIL-Acro II | √ | No scale base | 26 lb | Consult |

Ishida WIL-Acro II

Compact Label Printer

OPTIONS/ACCESSORIES

| PART # | DESCRIPTION | PRICE |
|--------|---------------------------|---------|
| 87514 | Additional label cassette | Consult |
| 174110 | SD memory card, 2GB | Consult |
| 160906 | USB flash memory 1GB | Consult |

COMMUNICATION

| PART # | DESCRIPTION | PRICE |
|---------|---|---------|
| 152628* | ScaleLink Pro 5 license file, one license required per computer | Consult |
| 78860 | Cross cable, Ethernet CAT5, 6ft | Consult |

*Software key is provided after purchase and online registration is completed at www.ricelake.com/ishida-software-form

NOTE: Manuals and software programs can be downloaded from the distributor section of www.ricelake.com/retail

LABEL STOCK

DESCRIPTION

Please refer to labels section of this catalog for ordering information and case quantity pricing

DIMENSIONS

WIL-ACRO II

| | | | |
|---|------------------|---|------------------|
| A | 7.1 in (182 mm) | F | 10.1 in (257 mm) |
| B | 8.8 in (224 mm) | G | 5.3 in (135 mm) |
| C | 14.2 in (360 mm) | H | 8.5 in (216 mm) |
| D | 14.6 in (370 mm) | I | 5.8 in (147 mm) |
| E | 8.9 in (226 mm) | | |

