



Approvals







Part Number/Price

Part #	Description	Est. Weight	Price
68502	TM-U590 ticket printer, 115/230 VAC power supply, cool white	12lb	Consult
128726	TM-U590 ticket printer, 115/230 VAC EU power supply, cool white	12lb	Consult
164391	TM-U590, 115/230 VAC power supply, cool white	12lb	Consult

Options/Accessories

Part #	Description	
68525	Ink cartridge (purple) ERC-31	Consult
104145	Ink cartridge (black) ERC-31B	Consult
23112	Power supply, U.S. version PS-180	Consult
128746	Power supply, European version of PS-180	Consult
111840	Protective dust cover	Consult
68562	Additional operating manual	Consult
68725	Technical manual	Consult
72309	Power supply, 12 VDC vehicle cigarette plug	Consult
Cables		
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable Cons	
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	
41279	25-pin D-sub male to nine-pin D-sub male, RS-232 with handshaking Interfaces to Rice Lake indicators with a serial port screw terminal connection	Consult
32810	25-pin D-sub male to eight-pin D-sub male, RS-232 with handshaking Interfaces with DC-190, DC-100, DC-200, DC-300	
Consult	Custom 20 mA/RS-232 serial interface cable	Consult

Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type.

Standard cable length is 5ft. \$2.00 charge for each additional foot.

Standard Features

- High-speed printing
- Single copy and up to five-part
- Wide slip capability of A4 size documents
- Remote-printing functionality sent via RS-232
- Supports double-strike commands

Specifications

Print Speed:

2.8 lines per second printing for 88 columns of print 4.9 lines per second printing for 40 columns of print

Print Width:

5.2 in

Paper Dimensions:

(L × W) 2.76 × 2.76 in/11.69 × 8.26 in (70 × 70 mm/297 × 210 mm)

Paper Thickness:

0.003 to 0.014 in (0.09 to 0.36 mm)

Interfaces:

Serial: Bidirectional parallel, RS-232 (DB-25F)/ RS-485 USB

Power:

24 VDC ± 10%

Ribbon:

ERC-31 (purple)

Dimensions:

(L × W × H) 10.47 × 9.92 × 7.28 in (266 × 252 × 185 mm)

Warranty:

One-year limited (includes printhead)

Approvals:

CE Listed FCC cULus Listed