








800-472-6703 www.ricelake.com



SALES AND TECHNICAL ASSISTANCE



The Equipoise is ideal for classrooms, laboratories and industrial applications. These seven-button balances allow quick access to 13 different units of measure, percentage, counting and accumulating.

A detachable enclosed weighing chamber is included in capacities below 1000 grams. Equipoise can be used with the included AC adaptor or an onboard rechargeable battery that offers up to 40 hours of continuous operation. RS-232 output is standard on each model. RS-232 cable is optional.





- LCD display
- Quick response
- Accumulation, counting and percentage modes
- 13 different units of measure
- Detachable enclosed weighing chamber (in capacities =1 kg)
- Battery operation for up to 40 hours of continuous use (without backlight)
- RS-232 interface for connecting to printer or PC
- Plastic enclosure

SPECIFICATIONS

WEIGHING UNITS: Gram, Ounce, Pound, Carat, Pennyweight, Troy Ounce, Grain

(See technical manual for complete listing)

OPERATING MODES: Weighing, Percent Weighing, Parts Counting, Accumulation

AC adapter (12 V/500 mA); internal rechargeable battery (6 V/1.2 Ah) POWER:

STABILIZATION TIME:

OPERATING

32 °F to 104 °F (0 °C to 40 °C)

TEMPERATURE:

EQ-300: 300 g, EQ-600: 600 g, EQ-1500: 1,500 g EQ-3000: 3,000 g, EQ-6000: 6,000 g **CALIBRATION WEIGHT:**

EST. WEIGHT: 6.6 lb (3 kg)

BATTERY LIFE: Up to 40 hours of continuous use (without backlight)

RETURN POLICY: Rice Lake standard policy WARRANTY: One-year limited APPROVAL: CE Marked

APPROVALS



Model	Capacity	Readability	Repeatability	Linearity	Pan Size	Weighing Chamber
EQ-300	300 g	0.01 g	0.01 g	0.02 g	Ø 4.7 in (120 mm)	6.7 × 5.7 × 3.1 in (170 × 145 × 80 mm)
EQ-600	600 g	0.02 g	0.02 g	0.04 g	Ø 4.7 in (120 mm)	6.7 × 5.7 × 3.1 in (170 × 145 × 80 mm)
EQ-1500	1,500 g	0.05 g	0.05 g	0.1 g	4.8 in × 5.6 in (122 mm × 142 mm)	N/A
EQ-3000	3,000 g	0.1 g	0.1 g	0.2 g	4.8 in × 5.6 in (122 mm × 142 mm)	N/A
EQ-6000	6,000 g	0.2 g	0.2 g	0.4 g	4.8 in × 5.6 in (122 mm × 142 mm)	N/A

