RoughDeck® HP
Forklift SENDit Portability Frames, NTEP **Standard Features** • Wireless connection from scale to operator display • Excitation to the load cell(s) provided by the transmitter, not the indicator • Each transmitter/receiver set is individually paired and will not interfere with another set • Transmitter excitation voltage: +4.8 VDC, 16×350 ohm or 32×700 ohm load cells • Estimated battery life of 100 hours Two set points with red/green display for operator verification Optional audible alarm Scale is sold separately (A) (B) **Approvals**



Part #	Size (W × L)	Est. Weight	Price		
Roughdeck HP Portability Frame					
210900	Roughdeck HP 4 × 4 ft, up to 10,000 lb capacity, frame only	350 lb	Consult		
210901	Roughdeck HP 5 × 5 ft, up to 10,000 lb capacity, frame only	395 lb	Consult		
SENDit Wireless Electronics Kit					
210899	Sendit wireless load cell interface kit, NTEP, Includes one 8004HD display	-	Consult		

Options/Accessories

<u> </u>		
Part #	Description	Price
162173	Battery, 6 V SLA	Consult
74574	Foot	Consult

Dimensions

Scale Size	4 × 4 ft	5 × 5 ft
Α	48.75 in	60.75 in
В	48.75 in	60.75 in
С	9.50 in	9.50 in

Note: 1 in=25.4 mm