

# Wi-Fi Information Request



Customer Number:

Company:  Name:

Date:  Phone:  Fax:  Email:

## Network Topology

*In order to customize a Wi-Fi module, the following information is required.*

Product:  Electronics Serial Number:

### Server (Soft AP):

*User's laptop or tablet is connecting directly to the scale.  
Only one module may be connected at a time in this mode.*

### Client:

*The scale connects to an existing router. This allows a laptop or tablet to connect to multiple scales at once.*

## Server Mode

SSID:

*The name for the network that the laptop/tablet is connecting to.*

### Security Mode:

**Open:** Allow anyone to connect to the scale

**WPA2:** Require a password to connect to the scale

Password:

*Only necessary if security mode is set to WPA2*

### DHCP:

**On:** Assign a dynamic IP to the scale. The laptop/tablet connecting to the scale may have a dynamic IP (RECOMMENDED)

**Off:** Assign a static IP to the scale. The laptop/tablet connecting to the scale must also have a static IP

IP Address-Static IP of the scale:

Net Mask/Gateway to assign to the scale:

Port used to connect to the scale (default 2000):

## Client Mode

SSID:

*The SSID of the router the scale will connect to.*

### Security mode of the router:

**Open:**

**WPA2:**

Password:

*This is the password used to connect to the router.*

### DHCP:

**On:** Allow the router to assign a dynamic IP to the scale (RECOMMENDED)

**Off:** Assign a static IP to the scale. This IP must be added to the static IP list in the router

IP Address-Static IP of the scale:

Net Mask/Gateway to assign to the scale:

Port used to connect to the scale (default 2000):