





NTEP Excluding 5K and 150K

WEIGH MODULES

Order Information

| Load Rating (Per Module) | Part# | Price | | | | | | | |
|--|-------|---------|--|--|--|--|--|--|--|
| Single Module (Does NOT Include Load Cell) | | | | | | | | | |
| 5,000 lb to 20,000 lb | 17943 | Consult | | | | | | | |
| 30,000 lb to 60,000 lb | 17944 | Consult | | | | | | | |
| 100,000 lb | 17945 | Consult | | | | | | | |
| 150,000 lb | 29011 | Consult | | | | | | | |
| 3-Module Kit | | | | | | | | | |
| 5,000 lb* | 36195 | Consult | | | | | | | |
| 40,000 lb | 36199 | Consult | | | | | | | |
| 4-Module Kit | | | | | | | | | |
| 5,000 lb* | 36203 | Consult | | | | | | | |
| 10,000 lb | 36204 | Consult | | | | | | | |
| 20,000 lb | 36205 | Consult | | | | | | | |
| 30,000 lb | 36206 | Consult | | | | | | | |
| 40,000 lb | 36207 | Consult | | | | | | | |
| 50,000 lb | 36208 | Consult | | | | | | | |
| 60,000 lb | 36209 | Consult | | | | | | | |
| 100,000 lb | 36210 | Consult | | | | | | | |
| 150,000 lb* | 43289 | Consult | | | | | | | |

| * | Non | -NTEP | Certified |
|---|-----|-------|-----------|
|---|-----|-------|-----------|

| Part# | Price | | | | | | | | | |
|-------------------------------|--------------------------|--|--|--|--|--|--|--|--|--|
| Dummy Load Cells (Mild Steel) | | | | | | | | | | |
| 33749 | Consult | | | | | | | | | |
| 74016 | Consult | | | | | | | | | |
| 94175 | Consult | | | | | | | | | |
| 158715 | Consult | | | | | | | | | |
| | | | | | | | | | | |
| 126419 | Consult | | | | | | | | | |
| | 74016 94175 158715 | | | | | | | | | |

Includes ground strap and mounting hardware per mount

Complete Kit Includes

- Three or four EZ Mount 1 stainless steel compression mounts with RL70000SS stainless steel double-ended shear beam load cells
- One JB4SS NEMA Type 4X stainless steel signal trim junction box
- 25 ft of hostile environment EL147HE SURVIVOR® load cell cable

Standard Features

- Capacities (per module): 5,000 to 150,000 lb
- NTEP Certified load cells (10 to 100 K)
- 304 stainless steel construction
- Unique sliding pin design compensates for thermal expansion/contraction
- Self-checking
- · Easy load cell replacement
- Simplified design allows bolting directly to tank
- · Center-loaded double-ended shear beam design
- · Low-profile design
- Compatible with VPG® Revere 9103 load cell

Optional Features

• Kits available with VPG Revere 9103 load cell, capacities in 5,000 to 150,000 lb

Applications

• Medium- to heavy-capacity tank and hopper weighing applications

Dimensions

| Rated Capacity | С | C1 | н | H1 | Н2 | L | L1 | L2 | L3 | L4 | T | w | W1 | W2 | W3 |
|-----------------------|------|------|-------|------|------|-------|-------|------|-------|------|---------------|-------|------|------|-------|
| lb/in | | | | | | | | | | | | | | | |
| 5,000 to 20,000 | 0.56 | 1.06 | 5.31 | 0.75 | 0.50 | 11.00 | 8.00 | 3.00 | 6.00 | 6.87 | 5/8-18 UNF | 7.50 | 4.00 | 3.00 | 6.00 |
| 30,000 to 60,000 | 0.68 | 1.19 | 8.43 | 1.00 | 0.75 | 15.00 | 11.50 | 5.12 | 8.00 | 8.50 | 1-14 UNS | 10.00 | 6.00 | 5.12 | 8.00 |
| 100,000 to 150,000 | 0.81 | 1.38 | 10.37 | 1.25 | 1.25 | 18.00 | 14.00 | 7.50 | 10.00 | 9.50 | 1-14 UNS | 12.00 | 9.00 | 7.50 | 10.00 |

