

Picture is a representation of actual product

Approvals






Order Information

Load Rating	Part#	Est. Weight	Price
5,000 kg	65854	3 lb	Consult
10,000 kg	65855	5 lb	Consult
20,000 kg	65856	8 lb	Consult
30,000 kg	65857	8 lb	Consult

Dimensions

Rated Capacity	A	В	С	D	E	Н
kg/mm						
5,000	80.0	19.0	70.0	20.0	33.4	30.0
10,000	92.0	28.0	80.0	14.6	33.4	33.0
20,000 to 30,000	110.0	29.0	101.5	26.3	39.0	50.0



Interchangeable Products

AVERY WEIGH-TRONIX®

220

Weigh Module Available

RICE LAKE WEIGHING SYSTEMS

220......page 43

Specifications

Full Scale Output:

2.0 mV/V

Output Resistance:

1,025 (± 20) ohm

Input Resistance:

1,065 (± 60) ohm

Material/Finish:

Stainless steel

Temperature:

Compensated: 14 °F to 104 °F (-10 °C to 40 °C)

Operating:

0°F to 150°F (-18°C to 65°C)

Seal Type:

Hermetically sealed, IP68

Safe Overload:

150% at center loading point, full scale

Rated Excitation:

5 to 10 VDC (15 V maximum)

Combined Error:

0.020% full scale

Insulation Resistance: 2,000 megohm

Deflection at Capacity:

< 0.5 mm at full scale

Cable Length:

5,000 kg: 5 m 10,000 to 20,000 kg: 10 m 30,000 kg: 20 m

Cable Diameter:

Polyurethane jacket

Cable Color Code:

Blue +Excitation

Black -Excitation White +Signal

Red -Signal

Green +Sense

Gray -Sense

Warranty:

5t, 10t

One-year limited

Approvals:

OIML cFMus