Onboard Weighing

TABLE OF CONTENTS

| PL Series Load Cells | 74 |
|---|-----|
| PL Series Tractor-Trailer Kits | 76 |
| PL Series Straight Truck Kits7 | 77 |
| TradeRoute [™] HL Series | 78 |
| Loadrunner® Onboard Weighing Systems | /80 |

ONBOARD WEIGHING

Product names, logos, brands and other trademarks featured or referred to within this publication are the property of their respective trademark holders.



PL Series Load Cells

PL9000-14



The PL9000-14 is a low-profile load cell designed for onboard weighing applications with limited height. With a singlepiece bearing plate and an overall profile of only 2.4 inches, the PL9000-14 is ideal for applications with four- or six-point under-body mounts and body rest mounts.

| Order Information Picture is a representation of actu | | | n of actual product | |
|---|-------------------|--------|---------------------|----------|
| Load Rating | | Part# | Est. Weight | Price |
| Static 16,500 lb | Dynamic 10,000 lb | 114322 | 19 lb | \$775.00 |

PL9000-14.4

The PL9000-14.4 is ideal for under-body and body rest mounts in four- or six-point system configurations. This load cell offers higher load ratings with a single-piece bearing plate and overall length of 14 inches.

| Order Information Picture is a representation of actual prod | | | | |
|--|-------------------|--------|-------------|----------|
| Load Rating | | Part# | Est. Weight | Price |
| Static 25,000 lb | Dynamic 12,500 lb | 115345 | 18lb | \$875.00 |

PL9000-22

The PL9000-22 is designed for underbody mounts and low-profile axle scales such as Rice Lake's AX3040. It has a 2.4-inch profile and is 22.6 inches long.

| Order Information Picture is a representation of actual | | | on of actual product | |
|---|-------------------|--------|----------------------|------------|
| Load Rating | | Part# | Est. Weight | Price |
| Static 30,000 lb | Dynamic 20,000 lb | 111766 | 30 lb | \$1,120.00 |

PL9000-26

2 ... 8

The PL9000-26 is a heavy duty, shear beam load cell designed for kingpin plates and underbody mounts. Available with either a single bearing plate or two separate bearing plates, the PL9000-26 has a 2.3 inch profile and is 26 inches long.

| D 1 |
|------------|
| Price |
| \$1,045.00 |
| _ |

PL9000-50

The PL9000-50 is designed for 5th wheel kits and spring suspension equalizer hangers. The PL9000-50 has two separate bearing plates, one on each end, and an overall profile of 2.8 inches.

| | | - | - | - |
|---------------|----------------|--------|-------------|---|
| • | 1 | 0 | - Carlo and | |
| Contra Longer | and the second | \sim | | |
| | | - | | |
| | | | | |

| Order Information Picture is a representation of actual production | | | | |
|--|-------------------|--------|-------------|----------|
| Load Rating | | Part# | Est. Weight | Price |
| Static 50,000 lb | Dynamic 12,500 lb | 114326 | 24 lb | \$890.00 |

PL9110

The PL9110 double-ended shear beam load cell is ideal for weighing equipment typically fixed to a truck body. This low-profile, rigid mount load cell is offered in capacities from 2,000 to 20,000 lbs with the same profile.



| Order Information Picture is a representation of actual product | | | | |
|---|--------|-------------|----------|--|
| Load Rating | Part# | Est. Weight | Price | |
| Static 2,000 lb | 204610 | 6 lb | \$780.00 | |
| Static 5,000 lb | 204611 | 6 lb | \$780.00 | |
| Static 10,000 lb | 204612 | 6 lb | \$780.00 | |
| Static 20,000 lb | 204613 | 6 lb | \$780.00 | |

PL9120



0 = 0

The PL9120 is designed for a mounting assembly that can be attached to a vertical surface. This perpendicular mounting design may be a solution where typical compression or tension mounts are not suited.

| Order Information | nformation Picture is a representation of actual product | | |
|-------------------|--|-------------|----------|
| Load Rating | Part# | Est. Weight | Price |
| Static 500 kg | 205775 | 5 lb | \$925.00 |

PL9200

The PL9200-25K onboard weighing load cell is hermetically sealed with an IP69 rating.

| Order Information | | Picture is a representatio | n of actual product |
|-------------------|--------|----------------------------|---------------------|
| Load Rating | Part# | Est. Weight | Price |
| 25,000 lb | 209603 | 25 lb | \$1,195.00 |
| 35,000 lb | 210812 | 25 lb | \$1,195.00 |
| | | | |

RLD-10K

The RLD-10K double-ended shear beam load cell has a low profile and rigid mount. The RLD-10K is ideal for applications where suspension mounts are not suitable, profile increases don't work, or dynamic forces are present.

| Order Information Picture is a representation of actual product | | | | |
|---|------------------|--------|-------------|------------|
| Load Rating | | Part# | Est. Weight | Price |
| Static 10,000 lb | Dynamic 4,000 lb | 120959 | 6 lb | \$1,260.00 |

PLSB-25K

The PLSB-25K is used in Rice Lake's twist-lock and stacking cone mount assemblies. This rigid mount, double-ended shear beam load cell is used when a series of mounts are not fixed to a frame at all times. The PLSB-25K can also be used in applications with dynamic forces.



| Order Information Picture is a representation of actual produ | | | | |
|---|-------------------|--------------|-------------|------------|
| Load Rating | | Part # | Est. Weight | Price |
| Static 25,000 lb | Dynamic 10,000 lb | 179827 | 26 lb | \$1,550.00 |
| Static 25,000 lb | Dynamic 10,000 lb | 191898179827 | 26 lb | \$1,550.00 |

LOAD PIN - 2 INCH, 20K



This 2-inch load pin is used in Rice Lake's Loadrunner kits and semi trailer landing gear. This load pin can be paired with load and support collars for applications that have pivot or rotation requirements.

| Order Information Picture is a representation of actual proc | | | on of actual product |
|--|--------|-------------|----------------------|
| Load Rating | Part# | Est. Weight | Price |
| 20,000 lb | 181895 | 10 lb | \$1,045.00 |

Additional details and complete specifications for onboard weighing load cells can be found online. Please consult the factory to determine the best model for your application.



PL Series Tractor-Trailer Kits

Part Number/Price

| Part # | Model # | Description | Price |
|------------|--------------------|---|-------------|
| Complete | Tractor/Trailer A | ir-Ride Kits | |
| 114285 | PL9700-100 | Single transducer kit (tractor/trailer) Kit includes: 9700, (2) air transmitter, (2) air pressure transducer, 35 ft & 80 ft truck cable, 15 ft power cable | \$3,200.00 |
| 114286 | PL9700-200 | Dual transducer kit (tractor/trailer) Kit includes: 9700, (2) air transmitter 2-lead, (2) dual air pressure transducer, 35 ft & 80 ft truck cable, 15 ft power cable | \$3,700.00 |
| 114287 | PL9704-3202 | Three channel air transducer system Kit includes: 9704, (3) air transmitter 2-lead, (3) dual air pressure transducer, (2) 35 ft & 80 ft truck cable, 15 ft power cable | \$5,200.00 |
| 114288 | PL9704-4202 | Four channel air transducer system Kit includes: 9704, (4) air transmitter 2-lead, (4) dual air pressure transducer, (3) 35 ft & 80 ft truck cable, 15 ft power cable | \$6,900.00 |
| 114289 | PL9704A-3202 | Three channel air transducer system with auto ID indicator/transmitter Kit includes: 9704A, (3) air transmitter 2-lead auto ID, (3) dual air pressure transducer, (2) 35 ft & 80 ft truck cable, 15 ft power cable | \$5,400.00 |
| 114290 | PL9704A-4202 | Four channel air transducer system with auto ID indicator Kit includes: 9704A, (4) air transmitter 2-lead auto ID, (4) dual air pressure transducer, (3) 35 ft & 80 ft truck cable, 15 ft power cable | \$6,900.00 |
| Half Syste | em Air-Ride Kits | | |
| 114292 | PL9701-200 | Dual transducer kit (tractor only) Kit includes: 9700, air transmitter 2-lead LC, dual air pressure transducer, 35 ft truck cable, 15 ft power cable | \$2,400.00 |
| 114294 | PL9701-200 | Dual transducer kit (trailer only) Kit includes: Air transmitter 2-lead LC, dual air pressure transducer, 80 ft truck cable | \$1,300.00 |
| Half Syste | em 5th Wheel Kit | S | |
| 114295 | PL9701-250H | Holland fixed 5th wheel kit (25,000 lb max with dead load) Kit includes: 9700, dual lead transmitter, (2) 5th wheel bending beam/suspension load cell, 35 ft truck cable, 15 ft power cable, hardware | \$4,400.00 |
| 168365 | - | Holland fixed 5th wheel kit with 9705 (25,000 lb max with dead load) Kit includes: 9705 with auto ID and selectable base, dual lead transmitter, 603-1 wireless transmitter, (5) 5th wheel bending beam/ suspension load cell, 35 ft truck cable, 15 ft power cable and hardware | \$5,500.00 |
| 114296 | PL9701-250F | Fontaine fixed 5th wheel kit (25,000 lb max with dead load) Kit includes: 9700, dual lead transmitter, (2) 5th wheel bending beam/suspension load cell, 35 ft truck cable, 15 ft power cable, hardware | \$4,300.00 |
| 168363 | - | Fontaine fixed 5th wheel kit with 9705 (25,000 lb max with dead load) Kit includes: 9705 with auto ID and selectable base, dual lead transmitter, 603-1 wireless transmitter, (5) 5th wheel bending beam/ suspension load cell, 35 ft truck cable, 15 ft power cable and hardware | \$5,200.00 |
| 132050 | PL9701-250J | JOST fixed 5th wheel kit (25,000 lb max with dead load) Kit includes: 9700, dual lead transmitter, (2) 5th wheel bending beam/suspension load cell, 35 ft truck cable, 15 ft power cable, hardware | \$4,800.00 |
| 168366 | - | JOST fixed 5th wheel kit with 9705 (25,000 lb max with dead load) Kit includes: 9705 with auto ID and selectable base, dual lead transmitter, 603-1 wireless transmitter, (5) 5th wheel bending beam/ suspension load cell, 35 ft truck cable, 15 ft power cable and hardware | \$5,400.00 |
| Equalizing | g Leaf Spring Sus | | |
| 114299 | PL9720-250 | Tandem axle center hanger load cell kit (25,000 lb max with dead load) Kit includes: Dual lead load cell transmitter, (2) 5th wheel bending beam/suspension load cell, 80 ft truck cable, (4) bearing plates, hardware | \$3,100.00 |
| 114300 | PL9720-450 | Tri-axle center hangers load cell kit (25,000 lb max with dead load) Kit includes: Four-lead load cell transmitter, (4) 5th wheel bending beam/suspension load cell, 80 ft truck cable, (8) bearing plates, hardware | \$5,200.00 |
| 163091 | - | Hutch center equalizer hanger for tandem/tri-axle kit Kit includes: Two hangers | \$2,400.00 |
| Tandem T | railer Single-Poir | it Suspension Kits | |
| 117667 | PL9720-216 | Single-point clamp load cell kit, 40,000 lb (80,000 lb max with dead load) Kit includes: Dual lead transmitter, (2) bearing plates, (2) 40,000 lb load cells,(8) bearing plates | \$3,800.00 |
| 161660 | - | Single-point clamp load cell kit, 40,000 lb (80,000 lb max with dead load) Kit includes: (2) 40,000 lb load cells, (4) body springs, (2) nuts, bolts and washers, bearing plates | \$3,000.00 |
| Logging k | | | |
| 182971 | - | North West short logger kit | \$16,500.00 |
| 182972 | | North West long logger Kit | \$7,900.00 |
| Indicator | | Dual-channel indicator kit | |
| 114163 | PL9700-02 | Kit includes: 9700, (2) dual lead transmitter, 35 ft & 80 ft truck cable, 15 ft power cable | \$2,400.00 |
| 114174 | PL9710-02 | Dual-channel indicator air kit with serial ports Kit includes: 9710, 2-lead transmitter, 2-lead air transmitter | \$2,800.00 |
| 114304 | PL9704-03 | Three-channel indicator air kit with serial ports Kit includes: 9704, (3) 2-lead air transmitter, 35 ft & (2) 80 ft truck cables, 15 ft power cable | \$3,700.00 |
| 114305 | PL9704-04 | Four-channel indicator air kit with serial ports Kit includes: 9704, (4) 2-lead air transmitter, 35 ft & (3) 80 ft truck cables, 15 ft power cable | \$4,100.00 |

Part Number/Price

| Part # | Model # | Description | Price |
|------------------|------------------|---|------------|
| Rigid Und | lerbody Load Cel | l Kits | |
| 114307 | PL9710-414.4 | Four-point indicator kit with 14.4 in load cells (50,000 lb max with dead load) Kit includes: 9710, four-lead transmitter, (4) 14.4 in load cell, (4) bearing plates, (4) body coil springs, 35 ft truck cable, 15 ft power cable | \$6,500.00 |
| 114308 | PL9710-614 | Six-point indicator kit with 14.4 in load cells (75,000 lb max with dead load) Kit includes: 9710, six-lead transmitter, (6) 14.4 in load cell, (6) bearing plates, (8) body coil springs, anti rotation plate, 35 ft truck cable, 15 ft power cable | \$8,400.00 |
| 114309 | PL9710-426 | Four-point indicator kit with 26 in load cells (50,000 lb max with dead load) Kit includes: 9710, four-lead transmitter, (4) 26 in load cells, (8) bearing plates, (6) body coil springs, 35 ft truck cable, 15 ft power cable | \$7,900.00 |
| 161660 | - | Single-point clamp load cell kit, 40,000 lb (80,000 lb max with dead load) Kit includes: (2) 40,000 lb load cells, (4) body springs, nuts, bolts and washers, bearing plates | \$3,000.00 |
| Tipping B | ody/Hoist Chass | is Kits | |
| 118572 | - | Six-point pivot pin kit with groove lock load cells, live weigh Kit includes: 9710, six-lead transmitter, 35 ft truck cable, 15 ft power cable, (4) bearing plates, (4) shear beam underbody load cells. (4) groove lock kits, (2) Labrie hinge pin kits (50,000 lb max with dead load) | \$9,600.00 |
| 178831 | | Three-point roll-off kit (Galbreath) includes: 9710, two-lead transmitter, 35 ft truck cable, 15 ft power cable | \$6,600.00 |
| Air-Ride | (its | | |
| 114313 | PL9700-1200 | Dual transducer/transmitter air ride kit Kit includes: 9700, two-lead air transmitter, air pressure transducer, 35 ft truck cable, 15 ft power cable | \$2,400.00 |
| 119287 | - | GPS indicator kit Kit includes: 9700/ RS-232 and GPS serial output, (2) dual lead air transmitters, Wireless transceiver, wireless receiver, 35 ft truck cable, 15 ft power cable | \$3,500.00 |
| 174310 | - | Smart pressure sensor | \$1,300.00 |
| Indicator | Kits | | |
| 114176 | PL9710-04 | Four-point indicator kit with serial ports Kit includes: 9710, four-lead transmitter, 35 ft truck cable, 15 ft power cable | \$2,300.00 |
| 114177 | PL9710-06 | Six-point indicator kit with serial ports Kit includes: 9710, six-lead transmitter, 35 ft truck cable, 15 ft power cable | \$2,400.00 |
| 171429 | - | In-cab display, single channel serial ports and load/deliver shrink calc software | \$1,095.00 |
| 174778 | - | In-cab display, dual channel with 10-key pad | \$2,500.00 |



TradeRoute[™] HL Series

Legal for Trade Onboard Weighing System



Approvals

ATP

Double-double Assembly



Single Assembly



Double Assembly

Standard Features

Legal for Trade Onboard System Includes

- 3 or 4 point onboard system RL20000 load cell with 20 ft cable, IP67
- 80-feet conduit cable
- Magnetic transport alarm sensor with 15 ft cable
- JB4SS junction box
- Hydraulic line locks and hoses
- 920i[®] Onboard Weigh Center
- Hydraulic pump not included
- Minimum 3,000 PSI recommended to maintain 2,200 PSI during lift

920i Onboard Weigh Center

- Epson® TM-U295 printer with splash shield
- Pre-installed 30 ft power cable, 30 ft load cell cable and inclinometer
- Transport alarm LEDs
- Power switch
- Start/End switch
- Waterproof enclosure
- Vibration mounts
- Mounting bracket to body not included

920i USB Universal with Onboard Software

- RS-232 port for connecting to ticket printer
- Standard onboard software

USB interface board only

- USB Interface Functions
 Available upon special request using a Type A sealed connection
- USB interface card on Port 2
- Supports weigh mode and configuration mode functions
- Supports upload of databases and 920i configuration file
- Supports download of databases, 920i configuration file, iRite[®], COD file and firmware file
- · Sanity checks for command errors
- Create STD database files

Flash Drives

- Supports USB 2.0 (optional)
- Create subdirectories by unit ID
 and database name
- Use the root directory for generic files

Specifications

Capacity:

Up to 60,000 lb (30,000 kg)

Load Cell:

Rice Lake RL20000I alloy steel S-Beam, 20 ft cable

Junction Box: JB4SS TuffSeal®

Rating/Material: NEMA Type 4X

- Stainless steel e nclosure Power Input:
- 9 to 36 VDC

Weigh Center: 920i[®] series weight controller Epson[®] TM-U295

Approvals:

NTEP CC 15-102 Class III/IIIL Measurement Canada AM-4847

Part Number/Price

| Part # | Model # | Description | Price |
|----------|------------------|---|-------------|
| TradeRou | ite Package (Inc | ludes 920i Weigh Center) | |
| 131098 | AN15L-3 | 15,000 lb × 5 lb/8,000 kg × 2 kg 3-point system, OB5-SGL5 / OB10-DBL5 modules | \$14,200.00 |
| 131099 | AN20L-4 | 20,000 lb × 5 lb/10,000 kg × 2 kg 4-point system, OB5-SGL5 / OB10-DBL5 modules | \$17,300.00 |
| 131100 | AN30L-3 | 30,000 lb × 10 lb/15,000 kg × 5 kg 3-point system, OB10-SGL10 / OB20-DBL10 modules | \$15,500.00 |
| 131101 | AN40L-4 | 40,000 lb × 10 lb/20,000 kg × 5 kg 4-point system, OB20-DBL10 (x2) modules | \$17,300.00 |
| 131103 | AN60L-4 | 60,000 lb × 10 lb/30,000 kg × 5 kg 4-point system, OB30-DBL15 (x2) modules | \$19,400.00 |
| System C | omponents | | |
| 131442 | - | 920i® Weigh Center package includes: Indicator, Epson® Ticket Printer, 25 ft load cell cable, power cable, housing, vibration mounts for installation to customer supplied mounting bracket | \$5,100.00 |
| 154109 | - | In-cab indicator 920i (requires 154112, 154111 and printer) | \$3,960.00 |
| 154112 | - | In-cab LED alarm assembly, 8 ft cable | \$120.00 |
| 154111 | - | Inclinometer, junction box assembly, 35 ft cable | \$720.00 |
| 65635 | - | Epson TM-U295 printer | \$630.00 |
| 131811 | - | Optional LED cab alarm, 35 ft | \$140.00 |
| 15494 | EL146HE | Four conductor hostile environment load cell cable | \$1.96/ft |
| 88956 | JB4SS | JB4SS signal trim j-box with PG37 cord grips | \$275.00 |
| 128123 | - | Conduit, 1/2 in non metallic liquid tight polytuf® | \$12.00/ft |
| 127617 | | Retrofit kit 10,000 lb eyebolts for 1 cell | \$390.00 |
| 128670 | 0B5-SGL5 | Low profile 5,000 lb single assembly | \$4,640.00 |
| 128666 | OB10-DLB5 | Low profile 10,000 lb double assembly | \$5,850.00 |
| 127956 | OB10-SGL10 | Low profile 10,000 lb single assembly | \$4,640.00 |
| 127958 | OB20-DBL10 | Low profile 20,000 lb double assembly | \$5,850.00 |
| 127959 | OB30-DBL15 | Low profile 30,000 lb double assembly | \$8,120.00 |
| 155300 | | Low profile 30,000 lb single tandem assembly | \$9,840.00 |
| 130107 | Packaging | Double/double packaging | \$180.00 |

Note: Connect to your existing hydraulic pump with a maximum pressure of 3,000 PSI with a minimum flow of 5 GPM for best performance of lifting speed. Note: Contact factory for other capacities not shown.



Loadrunner® Onboard Weighing Systems

Dump Truck Systems Kit



Part Number/Price

| Part # | Description | Price |
|--------|---|------------|
| System | | |
| 158195 | Dump truck system with 2-inch load pins, indicator, cables and hardware | \$4,900.00 |

780



Compatibility note: The Loadrunner dump truck kit has been designed for use on dual pin hinge pivot type dump bodies only. For dump truck body rear pivot assemblies using a single hinge bar, contact Rice Lake.