Ishida iPC Series



Approvals





Part Number/Price

Part #	Capacity	Platform Dimensions	Est. Weight	Price			
Single Display							
75466	100 oz	9.1 × 7.8 in	6 lb	Consult			
Single Display, Multi-ranging							
75454	6 lb (3 kg)	9.1 × 7.8 in	6 lb	Consult			
75455	15 lb (6 kg)	9.1 × 7.8 in	6 lb	Consult			
75457	30 lb (15 kg)	11 × 11.5 in	8 lb	Consult			
75458	60 lb (30 kg)	11 × 11.5 in	8 lb	Consult			

Options/Accessories


Part #	Description	Price
75470	Stainless steel platter cover (100 oz, 6 lb, and 15 lb capacity)	
75739	Stainless steel platter cover (30 lb and 60 lb capacity)	
75473*	AC adapter	Consult


*National Recognized Test Laboratory certified adapter


Dimensions

Ishida iPC Series					
Α	9.30 in	F	11.30 in		
В	9.10 in	G	11.00 in		
С	7.80 in	Н	11.50 in		
D	11.10 in	1	14.30 in		
Е	3.90 in	J	4.00 in		

Note: 1 in = 25.4 mm







Standard Features

- Six-digit liquid crystal display (LCD)
- Powered by two D cell batteries (up to 500 hours of operation)
- · Auto power-off function
- · Low battery indicator
- · Overload stops
- Batteries and AC adapter not included

Specifications

Display:

Six-digit (seven-segment), LCD Character height: 1 in (25.4 mm)

Keyboard:

Zero, tare, on/off, unit (lb/kg) NOTE: oz version only displays weight in oz

Power:

Two dry cell D type batteries* (up to 500 hours) or AC adapter Auto power-off function (can be set to 60 min., 20 min., or off)

Operational Temperature: 23 °F to 104 °F (-5 °C to 40 °C)

Divisions (Auto Ranging):

100 oz

0.05 oz: 0 to 50 oz 0.1 oz: 50 to 100 oz 6 lb

0.002 lb: 0 to 3 lb

0.005 lb: 3 to 6 lb 15 lb

0.005 lb: 0 to 6 lb

0.01 lb: 6 to 15 lb 30 lb 0.01 lb: 0 to 15 lb

0.02 lb: 15 to 30 lb 60 lb

0.02 lb: 0 to 30 lb 0.05 lb: 30 to 60 lb

Platter Size:

100 oz (3 kg): 9.1 × 7.8 in 6 lb (3 kg): 9.1 × 7.8 in 15 lb (6 kg): 9.1 × 7.8 in 30 lb (15 kg): 11 × 11.5 in 60 lb (30 kg): 11 × 11.5 in

Warranty:

One-year limited

Approvals:

NTEP Certified CC 02-139, Class III 0 to 30 lb 1,500 d; 60 lb 1,200 d; 0 to 100 oz 1000 d **UL** listed